

INDUSTRIAL COMPONENT DATA

2AMP 550V AC BS88 gG FUSE NIT2A NIT2 EATON ELECTRIC Fuse-link, LV, 40 A, AC 500 V, BS88, 21 x 129 mm, gL/gG,..

Brand: EATON - MOELLER | Manufacturer Part Number: 2AMP 550V AC BS88 gG FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	2AMP 550V AC BS88 gG FUSE
Catalog number	NIT2
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-5C7515776B
Generated	2026-08-06

Product Overview

Fuse-link, LV, 40 A, AC 500 V, BS88, 21 x 129 mm, gL/gG, BS

2AMP 550V AC BS88 gG FUSE

Fuse-link, LV, 2 A, AC 550 V, DC 250 V, BS88/A1, 14 x 56 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 2 A, AC 550 V, DC 250 V, BS88/A1, 14 x 56 mm, gL/gG, BS, offset bolted tags (slotted), general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder CM32FC RS20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number NIT2A EAN 5027590503921 UPC 051712392488 Product Length/Depth 56 mm Product Height 15 mm Product Width 15 mm Product Weight 15 g

Compliances CE Marked

RoHS Compliant Certifications IEC 60269-2

BS88 Electrical data

Amperage Rating 2 A Voltage rating 550 V Voltage type AC/DC Breaking capacity 80 kA Class Class gG/gL Compatible fuse holder

Suitable for CM32FC Camaster fuse holder

RS20 Red spot fuse holder Product specifications

Fuse type NIT Fitted with: Offset bolted tags Construction BS88/A1

ETIM for NIT2A Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

A1

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

550 V

Rated current (EF000227)

2 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

0.9 W

Mounting holes (EF021553)

Other

Centre-to-centre distance of connections (EF021151)

44.5 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 2AMP 550V AC BS88 gG FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.