

INDUSTRIAL COMPONENT DATA

2AMP 550V AC INDUSTRIALS AC2 DX-LN3-303 EATON ELECTRIC cartridge fuse, BT, 2 A, AC 550 V, BS88, 21 x 114mm, gL..

Brand: EATON - MOELLER | Manufacturer Part Number: 2AMP 550V AC INDUSTRIALS



Manufacturer	EATON - MOELLER
MPN / Reference	2AMP 550V AC INDUSTRIALS
Catalog number	DX-LN3-303
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-A71729505B
Generated	2026-08-06

Product Overview

cartridge fuse, BT, 2 A, AC 550 V, BS88, 21 x 114mm, gL/gG, BS

2AMP 550V AC INDUSTRIAL - Fuse-link, 2 A, AC 550 V, 80 kA, BS88, 21 x 114 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 2 A, AC 550 V, BS88, 21 x 114 mm, gL/gG, BS, centre-bolted tags, general industrial applications, BS88-1, IEC 60269-1, Breaking Capacity 80 kA, Ceramic body

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann fuses
--------------	---------------------------------

Additional Product Information

Fuse-link, 2 A, AC 550 V, 80 kA, BS88, 21 x 114 mm, gL/gG, BS Fuse, Fuse-link, low voltage, 2 A, AC 550 V, BS88, 21 x 114 mm, gL/gG, BS, centre-bolted tags, general industrial applications, BS88-1, IEC 60269-1, Breaking Capacity 80 kA, Ceramic body Delivery program

Product range Fuse Basic function Fuse-link Rated current [I]₂ A Rated voltage AC 550 V Construction size BS88 Size 21 x 114 mm Utilization category gL/gG Breaking Capacity 80 kA Usable for size/applications general industrial applications Standard/Approval BS Shape centre-bolted tags Material Ceramic body Standards/Regulations BS88-1 IEC 60269-1 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015]) Construction size Other Rated current 2 A Rated voltage 550 V Voltage type AC Rated switching capacity 80

kA Utilization category gL/gG (cable protection/equipment protection) Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No
ETIM for AC2 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
Other
Type of current (EF000143)
AC/DC
Rated voltage AC (EF007682)
550 V
Rated voltage DC (EF012281)
250 V
Rated current (EF000227)
2 A
Utilization category according to IEC 60269 (EF002572)
gG (cable protection/equipment...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 2AMP 550V AC INDUSTRIALS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.