

INDUSTRIAL COMPONENT DATA

2HD36 EATON ELECTRIC Fuse-link, high speed, 2 A, AC 1200 V, DC 750 V, 22 x 138 mm, gL/gG, BS

Brand: EATON - MOELLER | Manufacturer Part Number: 2HD36



Manufacturer	EATON - MOELLER
MPN / Reference	2HD36
Catalog number	10000
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-A4DD3B23E7
Generated	2026-08-06

Product Overview

2A 1200 VAC 750 VDC INDUSTRIAL FUSE

2HD36 - Fuse-link, high speed, 2 A, AC 1200 V, DC 750 V, 22 x 138 mm, gL/gG, BS

Fuse, Fuse-link, high speed, 2 A, AC 1200 V, DC 750 V, 22 x 138 mm, gL/gG, BS, offset bolted tags (slotted), traction, BS, Breaking Capacity 80 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, high speed, 2 A, AC 1200 V, DC 750 V, 22 x 138 mm, gL/gG, BS
Fuse, Fuse-link, high speed, 2 A, AC 1200 V, DC 750 V, 22 x 138 mm, gL/gG, BS, offset bolted tags (slotted), traction, BS, Breaking Capacity 80 kA

General specificationsProduct nameEaton Bussmann series high speed traction fusePart

no.2HD36EAN5027590472630Product Length/Depth136 millimetreProduct height22 millimetreProduct width22

millimetreProduct weight93.2 gramComplianceRoHS CompliantCertificationsBSProduct TradenameNoneProduct

TypeHigh speed traction fuseProduct Sub TypeNoneElectrical dataAmperage Rating2 AVoltage rating1200 VProduct

specificationsApplicationtractionFuse indicatorNoneTechnical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)Electric engineering, automation, process control

engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) ()

[BAB264011])Fuse construction type according to IEC 60269OtherType of currentAC/DCRated voltage AC1,200 VRated

voltage DC750 VRated current2 AUtilization categorygL/gG (cable protection/equipment protection)Breaking capacity80

kAColour codeNoneType of fuse status indicatorNonePower loss at rated current1.1 WMounting holesM5Centre-to-centre

distance of connections122.4 mm

ETIM for 2HD36 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 2HD36 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.