

INDUSTRIAL COMPONENT DATA

SEMI-COND FUSE 3000A 130V AC FWA-3000AH EATON ELECTRIC cartridge fuse, ultra rapid, 3000 A, AC 130v, 48 x 76..

Brand: EATON - MOELLER | Manufacturer Part Number: SEMI-COND FUSE 3000A 130V AC



Manufacturer	EATON - MOELLER
MPN / Reference	SEMI-COND FUSE 3000A 130V AC
Catalog number	FWA-3000AH
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-A349A86B5A
Generated	2026-08-06

Product Overview

cartridge fuse, ultra rapid, 3000 A, AC 130v, 48 x 76 mm, aR, UL

SEMI-COND FUSE 3000A 130V AC

Eaton Bussmann series FWA high speed fuse, 500 Vac (0.25-6.3A), 500 Vdc (2-5A), 3000A, 200 kAIC Vac, 50 kAIC at 120 Vdc, None, High speed fuse, Flush, Stud

Fuse, Fuse-link, high speed, 3000 A, AC 130 V, 48 x 76 mm, aR, UL, cylindrical with flush end, UL 248-13, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed cylindrical fuse Catalog Number FWA-3000AH EAN 5027590020374
UPC 051712795524 Product Length/Depth 10.2 mm Product Height 7.2 mm Product Width 10 mm Product Weight 1099 g
Compliances CE Marked

RoHS Compliant Certifications UL Recognized Electrical data

Amperage Rating 3000 A Voltage rating 130 Vac, 130 Vdc Voltage type AC/DC Interrupt rating 50 kAIC at 120 Vdc
200 kAIC Vac Class Class aR Pre arc (I2T) 2100000 Clearing (I2T) 5700000 Watt losses 150 W Product specification
Application Semiconductor, DC Common bus, DC drives, Power converters/rectifiers Fuse indicator Non Indicating

ETIM for FWA-3000AH Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

IEC 60269-4 flush end connections type B

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

130 V

Rated current (EF000227)

3000 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

200 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

150 W

Mounting holes (EF021553)

Other

Centre-to-centre distance of connections (EF021151)

47.6 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SEMI-COND FUSE 3000A 130V AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.