

INDUSTRIAL COMPONENT DATA

3.15Amp 500V SEMI-COND FUSE FWH-3.15A6F FWH-3-15A6F EATON ELECTRIC cartridge fuse, ultra rapid, 3.15 A, AC 5..

Brand: EATON - MOELLER | Manufacturer Part Number: 3.15Amp 500V SEMI-COND FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	3.15Amp 500V SEMI-COND FUSE
Catalog number	FWH-3-15A6F
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-5348361D2C
Generated	2026-08-06

Product Overview

cartridge fuse, ultra rapid, 3.15 A, AC 500 V, 6 x 32 mm, aR, UL

3.15Amp 500V SEMI-COND FUSE

3.15Amp 500V SEMI-COND FUSE - Fuse-link, high speed, 3.15 A, AC 500 V, 50 kA, 6 x 32 mm, aR, UL

Fuse, Fuse-link, high speed, 3.15 A, AC 500 V, 6 x 32 mm, aR, UL, cylindrical, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL 248, Breaking Capacity 50 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 3.15 A, AC 500 V, 50 kA, 6 x 32 mm, aR, UL
Fuse, Fuse-link, high speed, 3.15 A, AC 500 V, 6 x 32 mm, aR, UL, cylindrical, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL 248, Breaking Capacity 50 kA
Delivery program

Product range Fuse
Basic function Fuse-link
Field of application high speed
Rated current [I]_N 3.15 A
Rated voltage AC 500 V
Size 6 x 32 mm
Utilization category aR
Breaking Capacity 50 kA
Usable for size/applications protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage

starters
Standard/Approval UL
Shape cylindrical
Standards/Regulations UL 248
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) ()

[AFZ797013])
Size Other
Rated voltage 500 - 500 V
Rated voltage Other
Voltage type AC
Utilization category aR (accompanied semiconductor protection)
Rated operating frequency 45 - 62 Hz
Nominal current 3.15 A
With striker No
Release

characteristicOtherBreaking capacity50 kA
ETIM for FWH-3.15A6F Circuit breakers and fuses (EC002704)
Feature Name
Feature Value
Model (EF000010)
Ceramic fuse
Size (EF000088)
Other
Voltage type (EF000187)
AC
Rated current (EF000227)
3.15 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied semiconductor protection)
Type of fuse status indicator (EF004473...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 3.15Amp 500V SEMI-COND FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.