

INDUSTRIAL COMPONENT DATA

32A 660V SPECIAL BS88 FUSE 32HS07 EATON ELECTRIC

Fuse-link, high speed, 40 A, AC 690 V, DC 500 V, BS88, 18 x..

Brand: EATON - MOELLER | Manufacturer Part Number: 32A 660V SPECIAL BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	32A 660V SPECIAL BS88 FUSE
Catalog number	32HS07
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-A48A45C250
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 40 A, AC 690 V, DC 500 V, BS88, 18 x 96 mm, aR, BS

32A 660V SPECIAL BS88 FUSE

Fuse-link, low voltage, 32 A, DC 500 V, BS88/A2, 22 x 82 mm, BS

Fuse, Fuse-link, low voltage, 32 A, DC 500 V, BS88/A2, 22 x 82 mm, BS, offset bolted tags, Breaking Capacity 200 kA, Ceramic body, Optional accessories fuse-holder CM32F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number 32HS07 EAN 5027590476706

Product Length/Depth 23 mm Product Height 23 mm Product Width 83 mm Product Weight 51.65 g Compliances CE

RoHS Compliant

EAC Certifications BS88-2

IEC 60269-2 Electrical data

Amperage Rating 32 A Voltage rating 500 V Voltage type DC Breaking capacity 200 kA Product specifications

Fuse type HS07 Construction BS88/A2

ETIM for 32HS07 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)
Fuse system E
Fuse construction type according to IEC 60269 (EF015865)
A2
Type of current (EF000143)
DC
Rated voltage DC (EF012281)
500 V
Rated current (EF000227)
32 A
Utilization category according to IEC 60269 (EF002572)
Other
Breaking capacity (EF005617)
200 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
None
Power loss at rated current (EF012389)
3.5 W
Mounting holes (EF021553)
M5
Centre-to-centre distance of connections (EF021151)
71.5 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 32A 660V SPECIAL BS88 FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.