

INDUSTRIAL COMPONENT DATA

32AMP 415V AC TYPE J 32MJ30-8 EATON ELECTRIC Utility fuse-link, low voltage, 100 A, AC 415 V, BS88/J, 31 x 1..

Brand: EATON - MOELLER | Manufacturer Part Number: 32AMP 415V AC TYPE J



Manufacturer	EATON - MOELLER
MPN / Reference	32AMP 415V AC TYPE J
Catalog number	32MJ30-8
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-FE104EBAE0
Generated	2026-08-06

Product Overview

Utility fuse-link, low voltage, 100 A, AC 415 V, BS88/J, 31 x 110 mm, gL/gG, BS, 82mm fixing centres

32AMP 415V AC TYPE J

32AMP 415V AC TYPE J - Utility fuse-link, low voltage, 32 A, AC 415 V, 80 kA, BS88/J, 31 x 110 mm,gU, BS, 82 mm fixing centres

Fuse, Utility fuse-link, low voltage, 32 A, AC 415 V, BS88/J, 31 x 110 mm, gU, BS, dual bolted tags (slotted), 82 mm fixing centres, feeder pillars, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder JW3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

Utility fuse-link, low voltage, 32 A, AC 415 V, 80 kA, BS88/J, 31 x 110 mm,gU, BS, 82 mm fixing centresFuse, Utility fuse-link, low voltage, 32 A, AC 415 V, BS88/J, 31 x 110 mm, gU, BS, dual bolted tags (slotted), 82 mm fixing centres, feeder pillars, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder JW3Delivery program Product rangeFuseBasic functionUtility fuse-linkField of applicationlow voltageRated current [I]32 ARated voltageAC 415 VConstruction sizeBS88/JSize31 x 110 mmUtilization categorygUDescription82 mm fixing centresBreaking Capacity80 kAusable for size/applicationsfeeder pillarsStandard/ApprovalBS IECShapedual bolted tags (slotted)Standards/RegulationsBS88-2 IEC 60269-2Optional accessoriesfuse-holder JW3Technical data ETIM 7.0 Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015])Construction sizeOtherRated current32 ARated voltage415 VVoltage typeACRated switching capacity80 kAUtilization categoryOtherType of fuse status indicatorNoneInsulated metal gripping lugs (IMGL)No ETIM for 32MJ30-8 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

J

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

415 V

Rated current...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 32AMP 415V AC TYPE J with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.