

INDUSTRIAL COMPONENT DATA

32AMP 500V AC BS88 gG FUSE CEO32 EATON ELECTRIC

Fuse-link, LV, 50 A, DC 500 V, BS88/A3, 27 x 91 mm, gL/gG, BS

Brand: EATON - MOELLER | Manufacturer Part Number: 32AMP 500V AC BS88 gG FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	32AMP 500V AC BS88 gG FUSE
Catalog number	CEO32
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-CD99E9D55D
Generated	2026-08-06

Product Overview

Fuse-link, LV, 50 A, DC 500 V, BS88/A3, 27 x 91 mm, gL/gG, BS

32AMP 500V AC BS88 gG FUSE

Fuse-link, LV, 32 A, AC 500 V, BS88/A4, 25 x 110 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 32 A, AC 500 V, BS88/A4, 25 x 110 mm, gL/gG, BS, offset bolted tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder RS100H

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number CEO32 EAN 5027590496285

UPC 051712839457 Product Length/Depth 109.5 mm Product Height 24.5 mm Product Width 21 mm Product Weight 77.6

g Compliances CE Marked

RoHS Compliant Certifications BS88

IEC 60269

EAC Electrical data

Amperage Rating 32 A Voltage rating 500 V Voltage type AC Breaking capacity 80 kA Class Class gG/gL Compatible fuse holder

Suitable for RS100 Red spot fuse holder Product specifications
Fuse type CEO Fitted with: Offset bolted tags Construction BS88/A4
ETIM for CEO32 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Fuse system E
Fuse construction type according to IEC 60269 (EF015865)
A4
Type of current (EF000143)
AC
Rated voltage AC (EF007682)
500 V
Rated current (EF000227)
32 A
Utilization category according to IEC 60269 (EF002572)
gG (cable protection/equipment protection)
Breaking capacity (EF005617)
80 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
None
Power loss at rated current (EF012389)
3.5 W
Mounting holes (EF021553)
M8
Centre-to-centre distance of connections (EF021151)
94 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 32AMP 500V AC BS88 gG FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.