

INDUSTRIAL COMPONENT DATA

32AMP 550V AC BS88 FUSE NITD32 EATON ELECTRIC

Fuse-holder, low voltage, 32 A, AC 550 V, BS88/F1, 1P, BS, bac..

Brand: EATON - MOELLER | Manufacturer Part Number: 32AMP 550V AC BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	32AMP 550V AC BS88 FUSE
Catalog number	NITD32
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-C4E94E3CD2
Generated	2026-08-06

Product Overview

Fuse-holder, low voltage, 32 A, AC 550 V, BS88/F1, 1P, BS, back stud unit, white

32AMP 550V AC BS88 FUSE

Fuse-link, LV, 32 A, AC 550 V, BS88/A1, 14 x 55 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 32 A, AC 550 V, BS88/A1, 14 x 55 mm, gL/gG, BS, offset bolted tags (slotted), general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder CM32FC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number NITD32 EAN 5027590504119

UPC 051712840132 Product Length/Depth 55 mm Product Height 14 mm Product Width 14 mm Product Weight 15.5 g

Compliances RoHS Compliant

CE Marked Certifications IEC 60269-2

BS88 Electrical data

Amperage Rating 32 A Voltage rating 550 V Voltage type AC Breaking capacity 80 kA Class Class gG/gL Compatible fuse holder

Suitable for CM32FC Camaster fuse holder Product specifications

Fuse type NITD Fitted with: Offset bolted tags Construction BS88/A1

ETIM for NITD32 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

A1

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

550 V

Rated current (EF000227)

32 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

2.9 W

Mounting holes (EF021553)

Other

Centre-to-centre distance of connections (EF021151)

42.5 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 32AMP 550V AC BS88 FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.