

INDUSTRIAL COMPONENT DATA

32AMP 600V AC FERRULE 10 X 38MM FWC-32A10F EATON ELECTRIC Emergency-stop pushbutton, D 38mm, key unlocking, ..

Brand: EATON - MOELLER | Manufacturer Part Number: 32AMP 600V AC FERRULE 10 X 38MM



Manufacturer	EATON - MOELLER
MPN / Reference	32AMP 600V AC FERRULE 10 X 38MM
Catalog number	FWC-32A10F
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-177F4A1FEB
Generated	2026-08-06

Product Overview

Emergency-stop pushbutton, D=38mm, key unlocking, closure according to data

32AMP 600V AC FERRULE 10 X 38MM

Eaton Bussmann series FWC high speed cylindrical fuse, 600V (UL), 32A, 200 kAIC at 300 Vdc, 50 kAIC at 300 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceramic

Fuse, Fuse-link, high speed, 32 A, AC 600 V, 10 x 38 mm, aR, UL, cylindrical, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL248, Breaking Capacity 200 kA, Optional accessories fuse-holder CHM1DU

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed cylindrical fuse Catalog Number FWC-32A10F EAN 5027590420525

UPC 051712796484 Product Length/Depth 38 mm Product Height 11 mm Product Width 11 mm Product Weight 9.4 g

Compliances CE Marked

RoHS Compliant Certifications CSA Certified

UL Recognized Product specifications

Type High speed fuse Application Semiconductor, DC Common bus, DC drives, Power converters/rectifiers Amperage

Rating 32 A Accessories Breaking capacity 200 kA Frequency rating - max 62 Hz Frequency rating - min 45 Hz Fuse indicator Other Release characteristic Other Utilization category aR (accompanied semiconductor protection) Voltage type AC/DC Fuse size 10 x 38 mm Class Class aR Clearing (I₂T) 600 Watt losses 7.5 W Fuse shape Cylindrical Pre arc (I₂T) 95 Used with Finger safe holders/blocks and striker Color White Interrupt rating 200 kAIC Vac Connection Ferrule end x ferrule end Construction size 10 x 38 mm Material Ceramic Packaging type Standard Quantity 10 Voltage rating 600 V Fuse type FWC-A10F

ETIM for FWC-32A10F Circuit breakers and fuses (EC002704)

Feature Name

Feature Value

Model (EF000010)

Ceramic fuse

Size (EF000088)

10x38 mm

Voltage type (EF000187)

AC/DC

Rated current (EF000227)

32 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Type of fuse status indicator (EF004473)

Other

Release characteristic (EF000889)

Other

Power loss at rated current (EF012389)

7.5 W

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 32AMP 600V AC FERRULE 10 X 38MM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.