

INDUSTRIAL COMPONENT DATA

32FE EATON ELECTRIC Fuse-link, high speed, 32 A, AC 690 V, DC 500 V, BS88, 19 x 77 mm, aR, BS, low let-throu..

Brand: EATON - MOELLER | Manufacturer Part Number: 32FE



Manufacturer	EATON - MOELLER
MPN / Reference	32FE
Catalog number	10000
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-76CE01FDC9
Generated	2026-08-06

Product Overview

NOT STANDARD - MADE TO SPECIAL ORDER

Eaton Bussmann series high speed British standard fuse, Single barrel, 32A, 690 VAC/500 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 500 VDC

Fuse, Fuse-link, high speed, 32 A, AC 690 V, DC 500 V, BS88, 19 x 77 mm, aR, BS, offset bolted tags, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number 32FE Model Code NOT STANDARD - MADE TO SPECIAL ORDER EAN 5027590476683 UPC 051712422031 Product Length/Depth 90 mm Product Height 40 mm Product Width 80 mm Product Weight 38 g Compliances CE Marked

RoHS Compliant Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 32 A Breaking capacity 200 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 200 kA Rated voltage AC 690 V Rated voltage DC 500 V Center-to-center distance of connections 61.8 mm Mounting dimension M6 Current type AC/DC Class Class aR Fuse shape Offset bolted tags Color None Interrupt rating 200 kA RMS Sym, 50 kA at 500 Vdc Connection

Blade end x blade end Construction size Other Mounting method Stud Voltage rating 690 V (IEC), 700 V (UL) Fuse type FE
Suitable for EC-600 Trip indicator kit (indicator + clips)
TI700 Fuse indicator
MAI Microswitch/adaptor
MBI Microswitch/adaptor Fuse system (according to IEC 60269) Other
ETIM for 32FE Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
Other
Type of current (EF000143)
AC/DC
Rated voltage AC (EF007682)
690 V
Rated voltage DC (EF012281)
500 V
Rated cu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 32FE with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.