

## INDUSTRIAL COMPONENT DATA

# 32M35 500V AC BS88 FUSE AAO32M35 EATON ELECTRIC

## Fuse-link, high speed, 12 A, AC 690 V, DC 500 V, BS88, 19 x ..

Brand: EATON - MOELLER | Manufacturer Part Number: 32M35 500V AC BS88 FUSE



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | EATON - MOELLER         |
| MPN / Reference | 32M35 500V AC BS88 FUSE |
| Catalog number  | AAO32M35                |
| Category        | HRC fuse                |
| Minimum order   | 20 Pcs                  |
| Document ID     | EO-86ABF37B45           |
| Generated       | 2026-08-06              |

### Product Overview

Fuse-link, high speed, 12 A, AC 690 V, DC 500 V, BS88, 19 x 77 mm, aR, BS

32M35 500V AC BS88 FUSE

Fuse-link, low voltage, 32 A, AC 500 V, 80 kA, BS88/A2, 22 x 85 mm, gM, BS, motor-rated

Fuse, Fuse-link, low voltage, 32 A, AC 500 V, BS88/A2, 22 x 85 mm, gM, BS, offset bolted tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder CM32F RS32

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

### Additional Product Information

Fuse-link, low voltage, 32 A, AC 500 V, 80 kA, BS88/A2, 22 x 85 mm, gM, BS, motor-rated  
Fuse, Fuse-link, low voltage, 32 A, AC 500 V, BS88/A2, 22 x 85 mm, gM, BS, offset bolted tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder CM32F RS32  
Delivery program

Product range  
FuseBasic function  
Fuse-linkField of application  
low voltageRated current [I]  
32 AMotor current rating [I]  
32M35 ARated voltageAC 500 VConstruction sizeBS88/A2Size22 x 85 mmUtilization categorygMDescriptionmotor-ratedBreaking Capacity80 kAusable for size/applicationsgeneral industrial applicationsStandard/ApprovalBSShapeoffset bolted tagsStandards/RegulationsBS88-2

IEC 60269-2Optional accessoriesfuse-holder CM32F and RS32Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ([email protected]) [AFZ800015])Construction sizeOtherRated current32 ARated voltage500 VVoltage typeACRated switching capacity80

kAUtilization categoryOtherType of fuse status indicatorNoneInsulated metal gripping lugs (IMGL)No

ETIM for AAO32M35 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

A2

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

500 V

Rated current...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 32M35 500V AC BS88 FUSE with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.