

INDUSTRIAL COMPONENT DATA

32M40 415V AC BS88 FUSE NITD32M40 EATON ELECTRIC

Utility fuse-link, low voltage, 50 A, AC 415 V, BS88/J, 31 ..

Brand: EATON - MOELLER | Manufacturer Part Number: 32M40 415V AC BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	32M40 415V AC BS88 FUSE
Catalog number	NITD32M40
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-ED9CBF6899
Generated	2026-08-06

Product Overview

Utility fuse-link, low voltage, 50 A, AC 415 V, BS88/J, 31 x 131 mm, gL/gG, BS

32M40 415V AC BS88 FUSE

Fuse-link, LV, 32 A, AC 415 V, BS88/A1, 18 x 55 mm, gM, BS, 32M40

Fuse, Fuse-link, low voltage, 32 A, AC 415 V, BS88/A1, 18 x 55 mm, gM, BS, offset bolted tags (slotted), general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder CM32FC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number NITD32M40 EAN

5027590504126 UPC 051712844383 Product Length/Depth 57 mm Product Height 18 mm Product Width 18 mm Product Weight 27.05 g Compliances RoHS Compliant

CE Marked Certifications BS88

IEC 60269

EAC Electrical data

Amperage Rating 32 A Voltage rating 415 V Voltage type AC Breaking capacity 80 kA Class Class gM Compatible fuse holder

Suitable for CM32FC Camaster fuse holder Product specifications

Fuse type NITD Fitted with: Offset bolted tags Construction BS88/A1

ETIM for NITD32M40 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

A1

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

415 V

Rated current (EF000227)

32 A

Utilization category according to IEC 60269 (EF002572)

gM (motor protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

1.9 W

Mounting holes (EF021553)

M10

Centre-to-centre distance of connections (EF021151)

42.5 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 32M40 415V AC BS88 FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.