

INDUSTRIAL COMPONENT DATA

32M40A 660V AC / 460V DC gM FUSE TIA32M40 EATON ELECTRIC Fuse-link, LV, 32 A, AC 660 V, DC 460 V, BS88/A2, 2..

Brand: EATON - MOELLER | Manufacturer Part Number: 32M40A 660V AC / 460V DC gM FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	32M40A 660V AC / 460V DC gM FUSE
Catalog number	TIA32M40
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-6C41CBECF4
Generated	2026-08-06

Product Overview

32M40A 660V AC / 460V DC gM FUSE

Fuse-link, LV, 32 A, AC 660 V, DC 460 V, BS88/A2, 22 x 86 mm, gM, BS, 32M40

Fuse, Fuse-link, low voltage, 32 A, AC 660 V, DC 460 V, BS88/A2, 22 x 86 mm, gM, BS, offset bolted tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder CM32F RS32

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number TIA32M40 EAN 5027590514248

UPC 051712392938 Product Length/Depth 86 mm Product Height 23 mm Product Width 23 mm Product Weight 57.7 g

Compliances Contact Manufacturer Electrical data

Amperage Rating 40 A Voltage rating 660 V Voltage type AC/DC Breaking capacity 80 kA Class Class gM Compatible fuse holder

Suitable for CM32F Camaster fuse holder

RS32 Red spot fuse holder Product specifications

Fuse type TIA Fitted with: Offset bolted tags Construction BS88/A2

ETIM for TIA32M40 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

A2

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

660 V

Rated voltage DC (EF012281)

460 V

Rated current (EF000227)

40 A

Utilization category according to IEC 60269 (EF002572)

gM (motor protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Mounting holes (EF021553)

M5

Centre-to-centre distance of connections (EF021151)

73 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 32M40A 660V AC / 460V DC gM FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.