

INDUSTRIAL COMPONENT DATA

32M50 500V AC BS88 FUSE AAO32M50 EATON ELECTRIC

Fuse-link, high speed, 100 A, AC 690 V, DC 500 V, BS88, 19 x..

Brand: EATON - MOELLER | Manufacturer Part Number: 32M50 500V AC BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	32M50 500V AC BS88 FUSE
Catalog number	AAO32M50
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-C064BC4C25
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 100 A, AC 690 V, DC 500 V, BS88, 19 x 77 mm, aR, BS

32M50 500V AC BS88 FUSE

Fuse-link, LV, 32 A, AC 500 V, BS88/A2, 22 x 85 mm, gM, BS, 32M50

Fuse, Fuse-link, low voltage, 32 A, AC 500 V, BS88/A2, 22 x 85 mm, gM, BS, offset bolted tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder CM32F RS32

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number AAO32M50 EAN 5027590491587

UPC 051712838450 Product Length/Depth 85 mm Product Height 21 mm Product Width 21 mm Product Weight 50.1 g

Compliances RoHS Compliant Electrical data

Amperage Rating 50 A Voltage rating 500 V Voltage type AC Breaking capacity 80 kA Class Class gM Compatible fuse holder

Suitable for CM32F Camaster fuse holder

RS32 Red spot fuse holder Product specifications

Fuse type AAO Fitted with: Offset bolted tags Construction BS88/A2

ETIM for AAO32M50 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

A2

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

500 V

Rated current (EF000227)

50 A

Utilization category according to IEC 60269 (EF002572)

gM (motor protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Mounting holes (EF021553)

M5

Centre-to-centre distance of connections (EF021151)

73 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 32M50 500V AC BS88 FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.