

## INDUSTRIAL COMPONENT DATA

# TM355 EATON ELECTRIC Fuse-link, LV, 355 A, AC 660 V, DC 460 V, BS88/B4, 60 x 137 mm, gL/gG, BS

Brand: EATON - MOELLER | Manufacturer Part Number: TM355



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | TM355           |
| Catalog number  | 10000           |
| Category        | HRC fuse        |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-42DED03170   |
| Generated       | 2026-08-06      |

## Product Overview

355A 660V AC / 460V DC BS88 FUSE

Fuse-link, low voltage, 355 A, AC 660 V, DC 460 V, BS88/C1, 60 x 211 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 355 A, AC 660 V, DC 460 V, BS88/C1, 60 x 211 mm, gL/gG, BS, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder RS400

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Bussmann Series Low Voltage fuses and accessories

## Additional Product Information

## General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number TM355 EAN 5996516026571

Product Length/Depth 211 mm Product Height 60 mm Product Width 60 mm Product Weight 759 g Compliances CE

Marked

RoHS Compliant Certifications BS88

IEC 60269

EAC Electrical data

Amperage Rating 355 A Voltage rating 660 V Voltage type AC/DC Breaking capacity 80 kA Class Class gG/gL Compatible fuse holder

Suitable for RS400 Red spot fuse holder Product specifications

Fuse type TM Fitted with: Centre bolted tags Construction BS88/C1

ETIM for TM355 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

C1

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

660 V

Rated voltage DC (EF012281)

460 V

Rated current (EF000227)

355 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Mounting holes (EF021553)

M10

Centre-to-centre distance of connections (EF021151)

184 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TM355 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.