

INDUSTRIAL COMPONENT DATA

355AMP 240V AC BS88 FUSE 355LMT EATON ELECTRIC

Fuse-link, high speed, 6 A, AC 240 V, DC 150 V, BS88, 9 x 47 ..

Brand: EATON - MOELLER | Manufacturer Part Number: 355AMP 240V AC BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	355AMP 240V AC BS88 FUSE
Catalog number	355LMT
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-F1558F6B12
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 6 A, AC 240 V, DC 150 V, BS88, 9 x 47 mm, aR, BS
fuse cartridge, ultra fast, 355 A, AC 240 V, DC 150 V, BS88, 38 x 84 mm, aR, BS
Fuse-link, high speed, 355 A, AC 240 V, DC 150 V, 200 kA, BS88, 38 x 84 mm, aR, BS
Fuse, Fuse-link, high speed, 355 A, AC 240 V, DC 150 V, BS88, 38 x 84 mm, aR, BS, offset bolted tags, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-0111

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

Fuse-link, high speed, 355 A, AC 240 V, DC 150 V, 200 kA, BS88, 38 x 84 mm, aR, BS
Fuse, Fuse-link, high speed, 355 A, AC 240 V, DC 150 V, BS88, 38 x 84 mm, aR, BS, offset bolted tags, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-0111
Delivery program

Product range Fuse
Basic function Fuse-link
Field of application high speed
Rated current [I]_n 355 A
Rated voltage AC 240 V
DC 150 V
Construction size BS88
Size 38 x 84 mm
Utilization category aR
Breaking Capacity 200 kA
Usable for size/applications protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval BSS
Shape offset bolted tags
Standards/Regulations BS88-4
IEC 60269-4
Optional accessories fuse-holder BH-0111
Technical data ETIM 7.0
Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (
[AFZ800015])Construction sizeOtherRated current355 ARated voltage240 VVoltage typeAC/DCRated switching
capacity200 kAUtilization categoryOtherType of fuse status indicatorNoneInsulated metal gripping lugs (IMGL)No
ETIM for 355LMT Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Ty...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 355AMP 240V AC BS88 FUSE with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.