

INDUSTRIAL COMPONENT DATA

3.6KV 80AMP MOTOR START 3.6WFGHO780 3-6WFGHO780 EATON ELECTRIC Auxiliary winding switch, Contacts: 8, 20 A,

..

Brand: EATON - MOELLER | Manufacturer Part Number: 3.6KV 80AMP MOTOR START



Manufacturer	EATON - MOELLER
MPN / Reference	3.6KV 80AMP MOTOR START
Catalog number	3-6WFGHO780
Category	Medium-/high voltage fuse
Minimum order	3 Pcs
Document ID	EO-F7965D2014
Generated	2026-08-06

Product Overview

Auxiliary winding switch, Contacts: 8, 20 A, front plate: 2-START>0

Auxiliary winding switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 8, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, with spring-return from both directions to 0, 4 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: 2-START>0

Motor cartridge fuse, MT, 80 A, AC 3.6 kV, 76 x 432 mm, back-up, BS, with striker

3.6WFGHO780 - Motor fuse-link, medium voltage, 80 A, AC 3.6 kV, 76 x 432 mm, back-up, BS, with striker

Fuse, Motor fuse-link, medium voltage, 80 A, AC 3.6 kV, 76 x 432 mm, back-up, BS, with striker, cylindrical with offset bolted tags, motor protection, BS2692-1, Breaking Capacity 50 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories

Additional Product Information

Motor fuse-link, medium voltage, 80 A, AC 3.6 kV, 76 x 432 mm, back-up, BS, with striker Fuse, Motor fuse-link, medium voltage, 80 A, AC 3.6 kV, 76 x 432 mm, back-up, BS, with striker, cylindrical with offset bolted tags, motor protection, BS2692-1, Breaking Capacity 50 kA Delivery program

Product range Fuse Basic function Motor fuse-link Field of application medium voltage Rated current [I] 80 A Rated voltage

AC 3.6 kV Size 76 x 432 mm Utilization category back-up Status indicator with striker Breaking Capacity 50 kA usable for size/applications motor protection Standard/Approval BS Shape cylindrical with offset bolted tags Standards/Regulations BS2692-1 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507) Rated current 80 A Rated voltage 3.6 kV Voltage type AC Rated frequency 50 - 50 Hz Breaking capacity 50 kA Utilization category Other Application Motor protection Length 432 mm Diameter 76 mm Performance category according to IEC 60282-1 Back-up With striker Yes Standard British Standard Release characteristic Other Installation technique Air ETIM for 3.6WFGHO780 Circuit breakers and fuses (EC003507)

Feature Name

Feature Value

Rated current (EF000227)

80 A

Rated voltage (EF000228)

3.6 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Breaking capacity (EF005617)

0.05 kA

Utilization category according to IEC 60269 (EF002572)

Other

Length (EF001438)

442 mm

Performance category according to IEC 60282-1 (EF012539)

B...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 3.6KV 80AMP MOTOR START with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.