

INDUSTRIAL COMPONENT DATA

M22S-DI4-S-X7 286339 Y7-286339 EATON ELECTRIC 4-way pushbutton, black arrows, interlocked

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-DI4-S-X7



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-DI4-S-X7
Catalog number	Y7-286339
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-79E1593D51
Generated	2026-08-05

Product Overview

4-way pushbutton, black arrows, interlocked

M22S-DI4-S-X7

Eaton Moeller® series M22 Position pushbutton, RMQ-Titan, Actuators non-flush, momentary, 4-fold, opposing pushbuttons mechanically interlocked, Bezel: black, arrow up

Position pushbutton, Product range: RMQ-Titan, Single unit, Design: Actuators non-flush, momentary, Description: 4-fold, opposing pushbuttons mechanically interlocked, Name: 4 white arrows; black buttons, Degree of Protection: IP66, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 55 x 55, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 4-way pushbutton Catalog Number 286339 Model Code M22S-DI4-S-X7 EAN 4015082863395 Product Length/Depth 55 mm Product Height 32 mm Product Width 55 mm Product Weight 0.022 kg

Certifications IEC/EN 60947-5

UL File No.: E29184

CSA-C22.2 No. 14-05

UL Category Control No.: NKCR

CSA

UL
CSA Class No.: 3211-03
CSA-C22.2 No. 94-91
CE
IEC/EN 60947
CSA File No.: 012528
VDE 0660
UL 508
DNV
GL
LR Catalog Notes 4-fold Features & Functions
Bezel color Black Bezel material Plastic Design Non-Flush
Classical Features Labelled Fitted with: Front ring Functions Opposing pushbuttons mechanically interlocked Inscription 4 white arrows General
Degree of protection NEMA 4X
NEMA 12
IP66
NEMA 3R
NEMA 13 Degree of protection (front side) IP66
NEMA 4X Lifespan, mechanical 200,000 Operations Opening diameter 22.5 mm Operating frequency 3600 Operations/h
Product category RMQ-Titan Size Front dimensions: 55 x 55 mm Type Pushbutton Ambient conditions, mechanical
Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27
30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30 Communication
Connection to SmartWire-DT Yes
With SWD-RMQ connections Actuator
Actuating force 5 N Actuator color B...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-DI4-S-X7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.