

INDUSTRIAL COMPONENT DATA

M22-D4-S-X7 286336 Y7-286336 EATON ELECTRIC 4-way pushbutton, black arrows, momentary, silver

Brand: EATON - MOELLER | Manufacturer Part Number: M22-D4-S-X7



Manufacturer	EATON - MOELLER
MPN / Reference	M22-D4-S-X7
Catalog number	Y7-286336
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-01C29B1CD3
Generated	2026-08-03

Product Overview

4-way pushbutton, black arrows, momentary, silver

M22-D4-S-X7

Eaton Moeller® series M22 Position pushbutton, RMQ-Titan, Actuators non-flush, momentary, black, 4-fold, opposing pushbuttons not mechanically interlocked, Bezel: titanium, arrow up

Position pushbutton, Product range: RMQ-Titan, Single unit, Design: Actuators non-flush, momentary, Description: 4-fold, opposing pushbuttons not mechanically interlocked, Name: 4 white arrows; black buttons, Degree of Protection: IP66, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 55 x 55, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 4-way pushbutton Catalog Number 286336 Model Code M22-D4-S-X7 EAN 4015082863364 Product Length/Depth 55 mm Product Height 32 mm Product Width 55 mm Product Weight 0.022 kg

Compliances CE Marked Certifications CSA Std. C22.2 No. 14-05

EN 60947-5

IEC 60947-5

UL 508

CSA Std. C22.2 No. 94-91

VDE

CSA

CSA Class No.: 3211-03

CSA-C22.2 No. 14-05

CSA File No.: 012528

IEC/EN 60947

UL File No.: E29184

CSA-C22.2 No. 94-91

VDE 0660

CE

UL Category Control No.: NKCR

IEC/EN 60947-5

UL

DNV

GL

LR Catalog Notes 4-fold Features & Functions

Bezel color Titanium Bezel material Plastic Design Non-Flush

Classical Features Labelled Fitted with: Front ring Functions Opposing pushbuttons not mechanically interlocked Inscription
4 white arrows General

Degree of protection NEMA 13

NEMA 4X

NEMA 3R

IP66

NEMA 12 Degree of protection (front side) NEMA 4X

IP66 Lifespan, mechanical 200,000 Operations Opening diameter 22.5 mm Operating frequency 3600 Operations/h Product
category RMQ-Titan Size Front dimensions: 55 x 55 mm Type Pushbutton Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11
ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat,
constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Communicati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-D4-S-X7 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.