

INDUSTRIAL COMPONENT DATA

M22S-D4-S 279412 Y7-279412 EATON ELECTRIC 4-way pushbutton, black, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-D4-S



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-D4-S
Catalog number	Y7-279412
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-A9F20ACC37
Generated	2026-08-04

Product Overview

4-way pushbutton, black, momentary

M22S-D4-S

Eaton Moeller® series M22 Position pushbutton, RMQ-Titan, Actuators non-flush, momentary, 4-fold, opposing pushbuttons not mechanically interlocked, Bezel: black

Position pushbutton, Product range: RMQ-Titan, Single unit, Design: Actuators non-flush, momentary, Description: 4-fold, opposing pushbuttons not mechanically interlocked, Name: No inscription, actuator color black, Degree of Protection: IP66, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 55 x 55, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 4-way pushbutton Catalog Number 279412 Model Code M22S-D4-S EAN 4015082794125 Product Length/Depth 55 mm Product Height 32 mm Product Width 55 mm Product Weight 0.022 kg

Certifications CSA Class No.: 3211-03

IEC/EN 60947-5

VDE 0660

UL 508

CSA File No.: 012528

UL
CE
CSA
CSA-C22.2 No. 14-05
CSA-C22.2 No. 94-91
IEC/EN 60947
UL Category Control No.: NKCR
UL File No.: E29184
DNV
GL
LR Catalog Notes 4-fold Features & Functions
Bezel color Black Bezel material Plastic Design Non-Flush
Classical Fitted with: Front ring Functions Opposing pushbuttons not mechanically interlocked Inscription Blank General
Degree of protection IP66
NEMA 12
NEMA 3R
NEMA 4X
NEMA 13 Degree of protection (front side) IP66
NEMA 4X Lifespan, mechanical 200,000 Operations Opening diameter 22.5 mm Operating frequency 3600 Operations/h
Product category RMQ-Titan Size Front dimensions: 55 x 55 mm Type Pushbutton Ambient conditions, mechanical
Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27
30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat,
constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30 Communication
Connection to SmartWire-DT With SWD-RMQ connections
Yes Actuator
Actuating force 5 N Actuator color Black Actuator function Mome...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-D4-S with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.