

INDUSTRIAL COMPONENT DATA

M22-DI4-*-* 286340 Y7-286340 EATON ELECTRIC 4-way pushbutton, momentary, facility for inscription, interlock..

Brand: EATON - MOELLER | Manufacturer Part Number: M22-DI4-*-*



Manufacturer	EATON - MOELLER
MPN / Reference	M22-DI4-*-*
Catalog number	Y7-286340
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-E6CE59EFEF
Generated	2026-08-04

Product Overview

4-way pushbutton, momentary, facility for inscription, interlocked, silver

M22-DI4-*-*

Eaton Moeller® series M22 Position pushbutton, RMQ-Titan, Actuators non-flush, momentary, 4-fold, opposing pushbuttons mechanically interlocked, selectable, individual facility for inscription, Bezel: titanium

Position pushbutton, Product range: RMQ-Titan, Single unit, Design: Actuators non-flush, momentary, Description: 4-fold, opposing pushbuttons mechanically interlocked, button plate: selectable, Button plate individual facility for inscription, Degree of Protection: IP66, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 55 x 55, Ordering information: Notes on customized inscription -> Data sheet, additional product information (links), Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Auxiliary Control and Signalling Elements**

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 4-way pushbutton Catalog Number 286340 Model Code M22-DI4-*-* Product Length/Depth 55 mm Product Height 32 mm Product Width 55 mm Product Weight 0.022 kg Certifications CSA-C22.2 No. 94-91

CSA-C22.2 No. 14-05

UL 508

IEC/EN 60947-5

CSA Class No.: 3211-03

VDE 0660

UL File No.: E29184

CSA

CE

CSA File No.: 012528

IEC/EN 60947

UL Category Control No.: NKCR

UL

DNV

GL

LR Catalog Notes Notes on customized inscription -> Data sheet, additional product information (links) Features & Functions

Bezel color Chrome Bezel material Plastic Design Non-Flush

Classical Features Labelled Fitted with: Front ring Functions Opposing pushbuttons mechanically interlocked Inscription

Individual inscription possible General

Degree of protection NEMA 3R

NEMA 12

IP66

NEMA 4X

NEMA 13 Degree of protection (front side) IP66

NEMA 4X Lifespan, mechanical 200,000 Operations Opening diameter 22.5 mm Operating frequency 3600 Operations/h

Product category RMQ-Titan Size Front dimensions: 55 x 55 mm Type Pushbutton Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Communication

Connection to SmartWire-D...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-DI4-*-* with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.