

INDUSTRIAL COMPONENT DATA

40071353268 GUIDELED 10825 1-8H/D CGLINE+ SEILABH. EATON ELECTRIC GuideLed 10825 1-8h/D CGLine+ Seilabh.

Brand: EATON - MOELLER | Manufacturer Part Number: 40071353268



Manufacturer	EATON - MOELLER
MPN / Reference	40071353268
Catalog number	GUIDELED 10825 1-8H/D CGLINE+ SEILABH.
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-9038EDD8BC
Generated	2026-08-05

Product Overview

GuideLed 10825 1-8h/D CGLine+ Seilabh.

Eaton GuideLed mounting set for 10825, Exit sign, Ceiling wire suspension mounting, CGLine + technology, LED, Maintained / Non-Maintained operation, IP20, 1h/3h/8h selectable duration, requires LED panel

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Self contained
--------------	----------------------------------

Additional Product Information

ETIM for 40071353268 Luminaires (EC001957)

Feature Name

Feature Value

Mounting method (EF000003)

Pendant

Suitable for labelling type (EF001277)

Insert sheet/plate

Type of indicator (EF001278)

Single/double-sided

With pictogram (EF011099)

No

Monitoring equipment (EF008091)

Safety module for monitoring (central feeded system)

With remote switch connection (EF007947)

Yes

Power supply system (EF000233)

Peripheral (individual battery)

Battery technology (EF004351)

Lithium-ions

Lamp type (EF002423)

LED non-replaceable

With light source (EF005905)

No

Lamp holder (EF000048)

Other

Number of lighting heads (EF004258)

1

Housing material (EF001596)

Plastic

Housing colour (EF000136)

Grey

Material cover (EF004284)

Plastic opal

Voltage type (EF000187)

AC

Nominal voltage (EF005127)

220 V

Type of control gear (EF000381)

LED driver constant voltage

Light distributor (EF012170)

Diffuser

Rated life time L70/B50 at 25 °C (EF011870)

50000 h

Degree of protection (IP) (EF005474)

IP40

Impact strength (EF004293)

IK03

Protection class according to IEC 61140 (EF000004)

II

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Rated ambient temperature according to IEC 62722-2-1 (EF012090)

0 °C

Max. system power (EF009347)

5.1 W

Rated luminous flux according to IEC 62722-2-1 (EF009349)

115 lm

Power factor (EF025740)

0.89

Recognition distance (EF008732)

20 m

Nominal operation time (EF012518)

1 h

Width (EF000008)

80 mm

Height/depth (EF001456)

33 mm

Length (EF001438)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 40071353268 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.