

INDUSTRIAL COMPONENT DATA

40071353269 EATON ELECTRIC GuideLed 11821 1-8h/D CGLine+ Deckenm.

Brand: EATON - MOELLER | Manufacturer Part Number: 40071353269



Manufacturer	EATON - MOELLER
MPN / Reference	40071353269
Catalog number	40071353269
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-30226A2940
Generated	2026-08-05

Product Overview

GuideLed 11821 1-8h/D CGLine+ Deckenm.

GuideLed 11821 1-8h/D CGLine+ ceil. Kit

Eaton GuideLed mounting set for 11821, Exit sign, Ceiling mounting, CGLine + technology, LED, Maintained / Non-Maintained operation, IP20, 1h/3h/8h selectable duration, requires LED panel

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Central Battery System**

Additional Product Information

ETIM for 40071353269 Luminaires (EC001957)

Feature Name

Feature Value

Mounting method (EF000003)

Ceiling surface mounting

Suitable for labelling type (EF001277)

Insert sheet/plate

Type of indicator (EF001278)

Single/double-sided

With pictogram (EF011099)

No

Monitoring equipment (EF008091)

Safety module for monitoring (central feeded system)

With remote switch connection (EF007947)

Yes

Power supply system (EF000233)

Peripheral (individual battery)

Battery technology (EF004351)

Lithium-ions

Lamp type (EF002423)

LED non-replaceable

With light source (EF005905)

No

Lamp holder (EF000048)

Other

Number of lighting heads (EF004258)

1

Housing material (EF001596)

Plastic

Housing colour (EF000136)

Grey

Material cover (EF004284)

Plastic opal

Voltage type (EF000187)

AC

Nominal voltage (EF005127)

220 V

Type of control gear (EF000381)

LED driver constant voltage

Light distributor (EF012170)

Diffuser

Rated life time L70/B50 at 25 °C (EF011870)

50000 h

Degree of protection (IP) (EF005474)

IP40

Impact strength (EF004293)

IK03

Protection class according to IEC 61140 (EF000004)

II

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Rated ambient temperature according to IEC 62722-2-1 (EF012090)

0 °C

Max. system power (EF009347)

6.3 W

Rated luminous flux according to IEC 62722-2-1 (EF009349)

115 lm

Power factor (EF025740)

0.92

Recognition distance (EF008732)

30 m

Nominal operation time (EF012518)

1 h

Width (EF000008)

80 mm

Height/depth (EF001456)

33 mm

L...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 40071353269 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.