

INDUSTRIAL COMPONENT DATA

40071353271 GUIDELED 11823 1-8H/D CGLINE+PEND.1,5M EATON ELECTRIC GuideLed 11823 1-8h/D CGLine+Pend.1.5 m

Brand: EATON - MOELLER | Manufacturer Part Number: 40071353271



Manufacturer	EATON - MOELLER
MPN / Reference	40071353271
Catalog number	GUIDELED 11823 1-8H/D CGLINE+PEND.1,5M
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-534DEA5E2E
Generated	2026-08-05

Product Overview

GuideLed 11823 1-8h/D CGLine+Pend.1.5 m

Eaton GuideLed mounting set for 11823, Exit sign, Ceiling mounting rigid suspension with canopy 1,5m, CGLine + technology, LED, Maintained / Non-Maintained operation, IP20, 1h/3h/8h selectable duration, requires LED panel

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Self contained**

Additional Product Information

ETIM for 40071353271 Luminaires (EC001957)

Feature Name

Feature Value

Mounting method (EF000003)

Pendant

Suitable for labelling type (EF001277)

Insert sheet/plate

Type of indicator (EF001278)

Single/double-sided

With pictogram (EF011099)

No

Monitoring equipment (EF008091)
Safety module for monitoring (central feeded system)
With remote switch connection (EF007947)
Yes
Power supply system (EF000233)
Peripheral (individual battery)
Battery technology (EF004351)
Lithium-ions
Lamp type (EF002423)
LED non-replaceable
With light source (EF005905)
No
Lamp holder (EF000048)
Other
Number of lighting heads (EF004258)
1
Housing material (EF001596)
Plastic
Housing colour (EF000136)
Grey
Material cover (EF004284)
Plastic opal
Voltage type (EF000187)
AC
Nominal voltage (EF005127)
220 V
Type of control gear (EF000381)
LED driver constant voltage
Light distributor (EF012170)
Diffuser
Rated life time L70/B50 at 25 °C (EF011870)
50000 h
Degree of protection (IP) (EF005474)
IP40
Impact strength (EF004293)
IK03
Protection class according to IEC 61140 (EF000004)
II
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)
No
Rated ambient temperature according to IEC 62722-2-1 (EF012090)
0 °C
Max. system power (EF009347)
6.3 W
Rated luminous flux according to IEC 62722-2-1 (EF009349)
115 lm
Power factor (EF025740)

0.92

Recognition distance (EF008732)

30 m

Nominal operation time (EF012518)

1 h

Width (EF000008)

80 mm

Height/depth (EF001456)

33 mm

Length (EF001438)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 40071353271 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.