

INDUSTRIAL COMPONENT DATA

GuideLed SL 13811 1-8h/D CGLine+ 40071353275 EATON

ELECTRIC GuideLed SL 13811 1-8h/D CGLine+

Brand: EATON - MOELLER | Manufacturer Part Number: GuideLed SL 13811 1-8h/D CGLine+



Manufacturer	EATON - MOELLER
MPN / Reference	GuideLed SL 13811 1-8h/D CGLine+
Catalog number	40071353275
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-651A5C34D8
Generated	2026-08-05

Product Overview

GuideLed SL 13811 1-8h/D CGLine+

Eaton GuideLed SL 13811, Safety lighting, Recessed, Asymmetric optics for escape route, CGLine + technology, LED, Maintained / Non-Maintained operation, IP41, 204lm, 1h/3h/8h selectable duration

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Central Battery System**

Additional Product Information

GuideLed SL 13811 1-8h/D CGLine+, recessed mounting, with asymmetric optics for exit route lighting, LED-supply with CGLine+ technology in additional housing with strain relief, ceiling thickness 0 - 20 mm, white sim. RAL 9010

ETIM for 40071353275 Luminaires (EC001957)

Feature Name

Feature Value

Mounting method (EF000003)

Built-in

Suitable for labelling type (EF001277)

Other

With pictogram (EF011099)

No

Monitoring equipment (EF008091)

Safety module for monitoring (central feeded system)

With remote switch connection (EF007947)

Yes

Power supply system (EF000233)

Peripheral (individual battery)

Battery technology (EF004351)

Lithium-ions

Lamp type (EF002423)

LED non-replaceable

With light source (EF005905)

Yes

Lamp holder (EF000048)

Other

Number of lighting heads (EF004258)

1

Housing material (EF001596)

Plastic

Housing colour (EF000136)

Grey

Material cover (EF004284)

Plastic opal

Voltage type (EF000187)

AC

Nominal voltage (EF005127)

220 V

Type of control gear (EF000381)

LED driver constant current

Light distributor (EF012170)

Focal lens

Rated life time L70/B50 at 25 °C (EF011870)

50000 h

Degree of protection (IP) (EF005474)

IP41

Impact strength (EF004293)

IK03

Protection class according to IEC 61140 (EF000004)

II

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Rated ambient temperature according to IEC 62722-2-1 (EF012090)

0 °C

Max. system power (EF009347)

6.7 W

Rated luminous flux according to IEC 62722-2-1 (EF009349)

115 lm

Colour...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / GuideLed SL 13811 1-8h/D CGLine+ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.