

INDUSTRIAL COMPONENT DATA

40071353640 GUIDELED 1X026 CG-S WIRE SUSP. RECESSED EATON ELECTRIC GuideLed 1x026 CG-S Wire susp. recessed

Brand: EATON - MOELLER | Manufacturer Part Number: 40071353640



Manufacturer	EATON - MOELLER
MPN / Reference	40071353640
Catalog number	40071353640
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-ACBA56AABD
Generated	2026-08-06

Product Overview

GuideLed 1x026 CG-S Wire susp. recessed

Eaton GuideLed Rope mounting set 10026/11026 CG-S with ceiling cable holders, LED power supply and CG-S technology (20 addresses) for installation in the suspended ceiling, 20m & 30m, without pictogram

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Central Battery System

Additional Product Information

ETIM for 40071353640 Luminaires (EC001957)

Feature Name

Feature Value

Mounting method (EF000003)

Built-in

Function (EF000030)

Suitable for labelling type (EF001277)

Type of indicator (EF001278)

With pictogram (EF011099)

false

Monitoring equipment (EF008091)

Safety module for monitoring (central feeded system)

Suitable for standby switching (EF017055)

Suitable for continuous circuit (EF017056)
With remote switch connection (EF007947)
true
With remote control (EF000483)
Power supply system (EF000233)
Central (central battery)
Battery technology (EF004351)
Lamp type (EF002423)
With light source (EF005905)
false
Suitable for number of light sources (EF006436)
Lamp holder (EF000048)
Number of lighting heads (EF004258)
Housing material (EF001596)
Plastic
RAL-number housing (EF012502)
Housing colour (EF000136)
Grey
Material cover (EF004284)
Voltage type (EF000187)
DC
Nominal voltage (EF005127)
220 V
Nominal current (EF009345)
None mA
Type of control gear (EF000381)
LED operating device voltage-controlled
Exchangeable control gear (EF016286)
Light distributor (EF012170)
Max. number of luminaires per miniature circuit breaker B16 (MCB) (EF015534)
Energy efficiency class of the light source according to EU regulation 2019/2015 (EF016835)
Max. number of luminaires per miniature circuit breaker C16 (MCB) (EF015533)
Rated life time L70/B50 at 25 °C (EF011870)
None h
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq) (EF015687)
None %
Lumen maintenance at median use...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 40071353640 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.