

INDUSTRIAL COMPONENT DATA

400A 690V AC TYPE T FUSE 400MMT EATON ELECTRIC

Fuse-link, high speed, 700 A, AC 690 V, DIN 1, 53 x 66 x 138 ..

Brand: EATON - MOELLER | Manufacturer Part Number: 400A 690V AC TYPE T FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	400A 690V AC TYPE T FUSE
Catalog number	400MMT
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-73945A6BD6
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 700 A, AC 690 V, DIN 1, 53 x 66 x 138 mm, aR, DIN, IEC, type T indicator

400A 690V AC TYPE T FUSE

Eaton Bussmann series high speed British standard fuse, Double barrel, 400A, 690 VAC/350 VDC (IEC), 700 VAC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 350 VDC (IEC)

Fuse, Fuse-link, high speed, 400 A, AC 690 V, DC 350 V, BS88, 83 x 113 mm, aR, BS, centre bolted tags (dual barrel), protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-3133

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number 400MMT EAN 5027590046879

UPC 051712834940 Product Length/Depth 110 mm Product Height 83 mm Product Width 39 mm Product Weight 450 g

Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized

Designed and tested to BS88 part 4

IEC 60269-4

UL recognized Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 400 A
Breaking capacity 200 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category aR
(accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 200 kA Rated voltage AC 690 V
Rated voltage DC 350 V Center-to-center distance of connections 85 mm Mounting dimension Other Current type AC/DC
Class Class aR Clearing (I₂T) 150000 Watt losses 60 W Fuse shape Center dual barrel bolted tags Pre arc (I₂T) 21000
Color None Interrupt rating 200 kA RMS Sym (IEC/UL), 40 kA at 350 Vdc (IEC) Connection Blade end x blade end
Construction size Other Mounting method Stud Packaging type Standard Voltage rating 690 V (IEC), 700 V (UL) Fuse type
MMT Suitable for MC-700 Trip indicator kit (indicator + clips)
TI700 Fuse indicator
MAI Microswitch/adaptor
MBI Microswitch/adaptor Fuse system (according to IEC 60269) Other
ETIM for 400MMT Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
F...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 400A 690V AC TYPE T FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.