

INDUSTRIAL COMPONENT DATA

400A TRACTION FUSE 400RC EATON ELECTRIC Fuse-link, high speed, 400 A, DC 750 V, 73 x 231 mm, gL/gG, IEC

Brand: EATON - MOELLER | Manufacturer Part Number: 400A TRACTION FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	400A TRACTION FUSE
Catalog number	400RC
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-BE50526938
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 400 A, DC 750 V, 73 x 231 mm, gL/gG, IEC

400A TRACTION FUSE

Eaton Bussmann series high speed traction fuse, 690 Vac, 500 Vdc, 400A, None, Fuse, Class C gL/gG

Fuse, Fuse-link, high speed, 400 A, DC 750 V, 73 x 231 mm, gL/gG, IEC, centre-bolted tags, Auxiliary power and distribution protection, traction, IEC 60269-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed traction fuse Catalog Number 400RC EAN 5027590047081 UPC

051712565622 Product Length/Depth 231 mm Product Height 73 mm Product Width 73 mm Product Weight 45.3592 g

Compliances Contact factory Electrical data

Amperage Rating 400 A Voltage rating 750 V Voltage type DC Pre arc (I2T) 756000 Watt losses 48 W Breaking capacity 80 kA Class Class gG Product specification

Fuse size 73 x 231 mm

ETIM for 400RC Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

DC

Rated voltage DC (EF012281)

750 V

Rated current (EF000227)

400 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

48 W

Mounting holes (EF021553)

M10

Centre-to-centre distance of connections (EF021151)

196.6 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 400A TRACTION FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.