

INDUSTRIAL COMPONENT DATA

400AMP 690V THYRISTOR FUSE (1) 400CFMM EATON ELECTRIC 400AMP 690V THYRISTOR FUSE (1)

Brand: EATON - MOELLER | Manufacturer Part Number: 400AMP 690V THYRISTOR FUSE (1)



Manufacturer	EATON - MOELLER
MPN / Reference	400AMP 690V THYRISTOR FUSE (1)
Catalog number	400CFMM
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-7000AC74BB
Generated	2026-08-06

Product Overview

400AMP 690V THYRISTOR FUSE (1)

Fuse-link, high speed, 400 A, AC 690 V, DC 450 V, BS88, 83 x 136 mm, aR, BS

Fuse, Fuse-link, High Speed, 400 A, AC 690 V, DC 450 V, BS88, 38 x 136 mm, aR, BS, offset bolted tags (slotted), 110 mm fixing centres, traction, BS88-4, IEC 60269-4, Breaking Capacity 45 kA, Optional accessories, Supplied with

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 400 A, AC 690 V, DC 450 V, BS88, 83 x 136 mm, aR, BS Fuse, Fuse-link, high speed, 400 A, AC 690 V, DC 450 V, BS88, 83 x 136 mm, aR, BS, centre-bolted tags (dual barrel), 110 mm fixing centres, dual-barrel, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I]_n 400 A Rated voltage AC 690 V DC 450 V Construction size BS88 Size 83 x 136 mm Utilization category aR Standard/Approval BS Shape centre-bolted tags (dual barrel) Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015]) Construction size Other Rated current 400 A Rated voltage 690 V Voltage type AC/DC Rated switching capacity 200 kA Utilization category aR (accompanied semiconductor protection) Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No

ETIM for 400CFMM Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

690 V

Rated voltage DC (EF012281)

450 V

Rated current (EF000227)

400 A

Utilization category according to IEC 602...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 400AMP 690V THYRISTOR FUSE (1) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.