

INDUSTRIAL COMPONENT DATA

40AMP 415V AC INDUSTRIAL ESD40 EATON ELECTRIC cartridge fuse, BT 40 A, AC 415 V, BS88/F2, 18 x 68 mm, gL/gG,..

Brand: EATON - MOELLER | Manufacturer Part Number: 40AMP 415V AC INDUSTRIAL



Manufacturer	EATON - MOELLER
MPN / Reference	40AMP 415V AC INDUSTRIAL
Catalog number	ESD40
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-8CD7819591
Generated	2026-08-06

Product Overview

cartridge fuse, BT 40 A, AC 415 V, BS88/F2, 18 x 68 mm, gL/gG, BS

40AMP 415V AC INDUSTRIAL

Fuse-link, LV, 40 A, AC 415 V, BS88/F2, 18 x 68 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 40 A, AC 415 V, BS88/F2, 18 x 68 mm, gL/gG, BS, offset bladed tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder 63ENS SC63

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number ESD40 EAN 5027590498661
UPC 051712844598 Product Length/Depth 67 mm Product Height 18 mm Product Width 18 mm Product Weight 30.5 g

Compliances Contact Manufacturer Product specifications

Type Fuse Application general industrial applications Amperage Rating 40 A Fitted with: Offset bladed tags Fuse size BS88/F2 Current type AC Breaking capacity 80 kA Rated switching capacity 80 kA Rated voltage AC 415 V Class Class gG/gL Fuse type ESD Utilization category gL/gG (cable protection/equipment protection) Color None Interrupt rating 80 kAIC Fuse indicator None Insulated metal gripping lugs (IMGL) No Watt losses 3.2 W Connection Blade end Construction BS88/F2 Construction size F2 Fuse shape Offset bladed tags Voltage type AC Suitable for 63ENS Safeloc fuse holder

SC63 Safeclip fuse holder Voltage rating 415 V Fuse system (according to IEC 60269) Fuse system E
ETIM for ESD40 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

F2

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

415 V

Rated current (EF000227)

40 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated curren...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 40AMP 415V AC INDUSTRIAL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.