

INDUSTRIAL COMPONENT DATA

40AMP 500V AC / 250V DC BC40 BC40 EATON ELECTRIC Fuse-link, low voltage, 40 A, AC 500 V, DC 250 V, BS88, 21 ..

Brand: EATON - MOELLER | Manufacturer Part Number: 40AMP 500V AC / 250V DC BC40



Manufacturer	EATON - MOELLER
MPN / Reference	40AMP 500V AC / 250V DC BC40
Catalog number	BC40
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-62CFDE4578
Generated	2026-08-06

Product Overview

Fuse-link, low voltage, 40 A, AC 500 V, DC 250 V, BS88, 21 x 114 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 40 A, AC 500 V, DC 250 V, BS88, 21 x 114 mm, gL/gG, BS, centre-bolted tags, general industrial applications, BS88-1, IEC 60269-1, Breaking Capacity 80 kA, Ceramic body

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann fuses
--------------	---------------------------------

Additional Product Information

Fuse-link, low voltage, 40 A, AC 500 V, DC 250 V, BS88, 21 x 114 mm, gL/gG, BS Fuse, Fuse-link, low voltage, 40 A, AC 500 V, DC 250 V, BS88, 21 x 114 mm, gL/gG, BS, centre-bolted tags, general industrial applications, BS88-1, IEC 60269-1, Breaking Capacity 80 kA, Ceramic body [Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 40 A Rated voltage AC 500 V DC 250 V Construction size BS88 Size 21 × 114 mm Utilization category gL/gG Breaking Capacity 80 kA usable for size/applications general industrial applications Standard/Approval BS Shape centre-bolted tags Material Ceramic body Standards/Regulations BS88-1

IEC 60269-1 , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015]) Construction size Other Rated current 40 A Rated voltage 500 V Voltage type AC/DC Rated switching capacity 80 kA Utilization category gL/gG (cable protection/equipment protection) Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No]

ETIM for BC40 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

500 V

Rated voltage DC (EF0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 40AMP 500V AC / 250V DC BC40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.