

INDUSTRIAL COMPONENT DATA

40AMP 500V AC / 250V DC BD40 EATON ELECTRIC Fuse-link, LV, 40 A, AC 500 V, BS88, 21 x 129 mm, gL/gG, BS

Brand: EATON - MOELLER | Manufacturer Part Number: 40AMP 500V AC / 250V DC



Manufacturer	EATON - MOELLER
MPN / Reference	40AMP 500V AC / 250V DC
Catalog number	BD40
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-72EB4ED339
Generated	2026-08-06

Product Overview

Fuse-link, LV, 40 A, AC 500 V, BS88, 21 x 129 mm, gL/gG, BS

40AMP 500V AC / 250V DC

Fuse, Fuse-link, low voltage, 40 A, AC 500 V, BS88, 21 x 129 mm, gL/gG, BS, centre-bolted tags, general industrial applications, BS88, IEC 60269, Breaking Capacity 80 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number BD40 EAN 5027590492164 UPC 051712843614 Product Length/Depth 129 mm Product Height 21 mm Product Width 21 mm Product Weight 66.9 g

Compliances Contact Manufacturer Electrical data

Amperage Rating 40 A Voltage rating 500 V Voltage type AC

AC/DC Breaking capacity 80 kA Class Class gG/gL Product specifications

Fuse type BD Fitted with: Centre bolted tags Construction BS88

ETIM for BD40 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

500 V

Rated voltage DC (EF012281)

250 V

Rated current (EF000227)

40 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

4.7 W

Mounting holes (EF021553)

M8

Centre-to-centre distance of connections (EF021151)

111 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 40AMP 500V AC / 250V DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.