

INDUSTRIAL COMPONENT DATA

40AMP 700V ac 22 X 58MM FERRULE FWP-40A22F EATON ELECTRIC Fuse-link, high speed, 100 A, AC 700 V, 22 x 58 mm..

Brand: EATON - MOELLER | Manufacturer Part Number: 40AMP 700V ac 22 X 58MM FERRULE



Manufacturer	EATON - MOELLER
MPN / Reference	40AMP 700V ac 22 X 58MM FERRULE
Catalog number	FWP-40A22F
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-D0D646C717
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 100 A, AC 700 V, 22 x 58 mm, aR, UL

40AMP 700V ac 22 X 58MM FERRULE

Eaton Bussmann series FWP high speed fuse, 700 Vac (IEC), 700 Vdc (UL), 40A, 200 kAIC at 300 Vdc, 50 kAIC at 300 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceramic

Fuse, Fuse-link, high speed, 40 A, AC 700 V, 22 x 58 mm, aR, UL, cylindrical, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL248, Breaking Capacity 200 kA, Optional accessories fuse-holder CH221B

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed cylindrical fuse Catalog Number FWP-40A22F EAN 5027590500739

UPC 051712796552 Product Length/Depth 58 mm Product Height 23 mm Product Width 23 mm Product Weight 59.9 g

Compliances CE Marked

RoHS Compliant Certifications UL Recognized

CSA Certified Product specifications

Type High speed fuse Application Semiconductor, DC Common bus, DC drives, Power converters/rectifiers Amperage

Rating 40 A Accessories JM70100 Fuse base Breaking capacity 200 kA Frequency rating - max 62 Hz Frequency rating - min 45 Hz Fuse indicator Other Release characteristic Other Utilization category aR (accompanied semiconductor protection) Voltage type AC/DC Fuse size 22 x 58 mm Class Class aR Clearing (I2T) 960 Watt losses 12 W Fuse shape Cylindrical Minimum melting 68 I2t (A2 sec) Pre arc (I2T) 68 Used with Finger safe holders/blocks and striker Color White Interrupt rating 200 kAIC Connection Ferrule end x ferrule end Construction size 22 mm x 58 mm Material Ceramic Packaging type Standard Quantity 10 Voltage rating 700 V Fuse type FWP-A22F
ETIM for FWP-40A22F Circuit breakers and fuses (EC002704)

Feature Name

Feature Value

Model (EF000010)

Ceramic fuse

Size (EF000088)

22x58 mm

Voltage type (EF000187)

AC/DC

Rated current (EF000227)

40 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Type of fuse status indicator (EF004473)

Other

Release characteristic (EF000889)

Other

Power loss at....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 40AMP 700V ac 22 X 58MM FERRULE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.