

INDUSTRIAL COMPONENT DATA

40MJ25-6 40Amp 415Vac FEEDER PILLAR FERRULE FUSE EATON ELECTRIC cartridge fuse of Utility, BT, 40, AC 415 V,..

Brand: EATON - MOELLER | Manufacturer Part Number: 40MJ25-6



Manufacturer	EATON - MOELLER
MPN / Reference	40MJ25-6
Catalog number	40Amp 415Vac FEEDER PILLAR FERRULE FUSE
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-D21DECB51F
Generated	2026-08-06

Product Overview

cartridge fuse of Utility, BT, 40, AC 415 V, BS88/J, 39 x 46 mm, gL/gG, BS

40Amp 415Vac FEEDER PILLAR FERRULE FUSE

40Amp 415Vac FEEDER PILLAR FERRULE FUSE - Utility fuse-link, low voltage, 40 A, AC 415 V, BS88/J, 39 x 46 mm, gL/gG, BS

Fuse, Utility fuse-link, low voltage, 40 A, AC 415 V, BS88/J, 39 x 46 mm, gU, BS, cylindrical, feeder pillars, BS88, Breaking Capacity 80 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories
--------------	---

Additional Product Information

Utility fuse-link, low voltage, 40 A, AC 415 V, BS88/J, 39 x 46 mm, gL/gG, BSFuse, Utility fuse-link, low voltage, 40 A, AC 415 V, BS88/J, 39 x 46 mm, gL/gG, BS, cylindrical, feeder pillars, BS88, Breaking Capacity 80 kADelivery program
Product rangeFuseBasic functionUtility fuse-linkField of applicationlow voltageRated current [I]40 ARated voltageAC 415 VConstruction sizeBS88/JSize39 x 46 mmUtilization categorygL/gGBreaking Capacity80 kAusable for
size/applicationsfeeder pillarsStandard/ApprovalBSShapecylindricalStandards/RegulationsBS88Technical data ETIM 7.0
Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015])Construction sizeOtherRated current40 ARated voltage415 VVoltage typeACRated switching capacity80 kAUtilization categorygL/gG (cable protection/equipment protection)Type of fuse status indicatorNoneInsulated metal gripping lugs (IMGL)No

ETIM for 40MJ25-6 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Rated current (EF000227)

40 A

Utilization category according to IEC 60269 (EF002572)

Other

Breaking capacity (EF005617)

80 kA

Type of fuse status indicator (EF004473)

None

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 40MJ25-6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.