

INDUSTRIAL COMPONENT DATA

40NHG000B-400 EATON ELECTRIC Fuse-link, LV, 100 A, AC 400 V, NH000, gL/gG, IEC, dual indicator, live grippin..

Brand: EATON - MOELLER | Manufacturer Part Number: 40NHG000B-400



Manufacturer	EATON - MOELLER
MPN / Reference	40NHG000B-400
Catalog number	40NHG000B400
Category	Low Voltage HRC fuse
Minimum order	3 Pcs
Document ID	EO-19470E7F9D
Generated	2026-08-06

Product Overview

Fuse-link, LV, 100 A, AC 400 V, NH000, gL/gG, IEC, dual indicator, live gripping lugs

cartridge fuse, BT 40 A, AC 400 V, NH000, gL/gG, IEC, indicator double, metal terminals

40NHG000B-400 - Fuse-link, LV, 40 A, AC 400 V, NH000, gL/gG, IEC, dual indicator, live gripping lugs

Fuse, fuse-link, low voltage, 40 A, AC 400 V, NH000, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann EWS fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage NH Fuse Catalog Number 40NHG000B-400 EAN 5027590480260

Product Length/Depth 79 mm Product Height 51 mm Product Width 21 mm Product Weight 130.667 g Compliances CE Marked

RoHS Compliant Certifications IEC 60269-1

IEC 60269-2

DIN 43620 Electrical data

Amperage Rating 40 A Voltage rating 400 V Voltage type AC Breaking capacity 120 kA Class Class gG/gL Frequency rating - min 45 Hz Frequency rating - max 62 Hz Product specification

Fuse size NH000 Insulated metal gripping lugs (IMGL) No Accessories

Suitable for Microswitch 170H0236

EBF Vertical fuse rail
EBV Vertical fuse switch-disconnectors
EBH Size 000 Horizontal fuse switch-disconnectors
ETIM for 40NHG000B-400 Circuit breakers and fuses (EC000055)
Feature Name
Feature Value
Fuse construction type according to IEC 60269 (EF015865)
NH000
Voltage type (EF000187)
AC
Rated current (EF000227)
40 A
Rated voltage AC (EF007682)
415 V
Rated switching capacity AC (EF017698)
120 kA
Utilization category according to IEC 60269 (EF002572)
gG (cable protection/equipment protection)
Type of fuse status indicator (EF004473)
Combination fuse status indicator
Insulated metal gripping lugs (IMGL) (EF012538)
No
Power loss at rated current (EF012389)
3 W

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 40NHG000B-400 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.