

INDUSTRIAL COMPONENT DATA

45A 690V AC TYPE T FUSE 45FE EATON ELECTRIC Fuse-link, high speed, 400 A, AC 690 V, DIN 00, 30 x 51 x 100 mm..

Brand: EATON - MOELLER | Manufacturer Part Number: 45A 690V AC TYPE T FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	45A 690V AC TYPE T FUSE
Catalog number	45FE
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-FDDED2917C6
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 400 A, AC 690 V, DIN 00, 30 x 51 x 100 mm, aR, DIN, IEC, type T indicator

45A 690V AC TYPE T FUSE

Eaton Busmann series high speed British standard fuse, Single barrel, 45A, 690 VAC/500 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym.HS, 50 kA DC at 500 VDC

Fuse, Fuse-link, high speed, 45 A, AC 690 V, DC 500 V, BS88, 19 x 77 mm, aR, BS, offset bolted tags, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-0111

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Busmann series high speed british standard fuse Catalog Number 45FE EAN 5027590480796 UPC 051712835244 Product Length/Depth 76 mm Product Height 20 mm Product Width 20 mm Product Weight 40.6 g

Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated

Designed and tested to BS88 part 4

IEC 60269-4 Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 45 A

Breaking capacity 200 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 200 kA Rated voltage AC 690 V Rated voltage DC 500 V Center-to-center distance of connections 62 mm Mounting dimension M6 Current type AC/DC Class Class aR Clearing (I2T) 270 at 415 V, 450 at 660 V Watt losses 11 W Fuse shape Offset bolted tags Pre arc (I2T) 76 Color None Interrupt rating 200 kA RMS Sym, 50 kA at 500 Vdc Connection Blade end x blade end Construction size Other Mounting method Stud Packaging type Standard Voltage rating 690 V (IEC), 700 V (UL) Fuse type FE Suitable for EC-600 Trip indicator kit (indicator + clips)
TI700 Fuse indicator
MAI Microswitch/adaptor
MBI Microswitch/adaptor Fuse system (according to IEC 60269) Other
ETIM for 45FE Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 45A 690V AC TYPE T FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.