

INDUSTRIAL COMPONENT DATA

46KV 100 AMP LINK 46KD100 46KD100 DS7-FAN-100 EATON ELECTRIC Cartridge fuse, expulsion, MT, 100 A, AC 46 kV,..

Brand: EATON - MOELLER | Manufacturer Part Number: 46KV 100 AMP LINK 46KD100



Manufacturer	EATON - MOELLER
MPN / Reference	46KV 100 AMP LINK 46KD100
Catalog number	DS7-FAN-100
Category	Expulsion fuse-link, medium voltage
Minimum order	10 Pcs
Document ID	EO-A54EBEECC5
Generated	2026-08-06

Product Overview

Cartridge fuse, expulsion, MT, 100 A, AC 46 kV, 787 mm, ANSI a, K fast

Fuse cartridge ejection, MT, 100 A, AC 46 kV, 787 mm, ANSI, K fast

46KD100 - Expulsion fuse-link, medium voltage, 100 A, AC 46 kV, 787 mm, ANSI, K fast, style D termination

Fuse, Expulsion fuse-link, medium voltage, 100 A, AC 46 kV, 787 mm, ANSI, K fast, Double tailed link without NEMA button head, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann fuses
--------------	---------------------------------

Additional Product Information

Expulsion fuse-link, medium voltage, 100 A, AC 46 kV, 787 mm, ANSI, K fast, style D termination Fuse, Expulsion fuse-link, medium voltage, 100 A, AC 46 kV, 787 mm, ANSI, K fast, Double tailed link without NEMA button head, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA Delivery program

Product range Fuse Basic function Expulsion fuse-link Field of application medium voltage Rated current [I] 100 A Rated voltage AC 46 kV Size 787 mm Description Double tailed link without NEMA button head Breaking Capacity 8 kA usable for size/applications protection of transformer primary side, feeder, capacitor bank Release characteristic [class] K fast

Standard/Approval ANSI Standards/Regulations ANSI C37-42

ETIM for 46KD100 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated current (EF000227)

100 A
Rated voltage (EF000228)
46 kV
Voltage type (EF000187)
AC
Rated frequency (EF001663)
50 Hz
Release characteristic (EF000889)
K
Type of termination (EF012540)
Double tail
Standard (EF009322)
ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 46KV 100 AMP LINK 46KD100 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.