

INDUSTRIAL COMPONENT DATA

46KBR100 EATON ELECTRIC Fuse-link, high speed, 100 A, AC 250 V

Brand: EATON - MOELLER | Manufacturer Part Number: 46KBR100



Manufacturer	EATON - MOELLER
MPN / Reference	46KBR100
Catalog number	10000
Category	Expulsion fuse-link, medium voltage
Minimum order	10 Pcs
Document ID	EO-863F4FC0A8
Generated	2026-08-06

Product Overview

46KV 100A REMOVABLE B/H EXPULSION LINK

46KBR100 - Expulsion fuse-link, medium voltage, 100 A, AC 46 kV, 787 mm, ANSI, K fast

Fuse, Expulsion fuse-link, medium voltage, 100 A, AC 46 kV, 787 mm, ANSI, K fast, removable NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories

Additional Product Information

Expulsion fuse-link, medium voltage, 100 A, AC 46 kV, 787 mm, ANSI, K fast
Fuse, Expulsion fuse-link, medium voltage, 100 A, AC 46 kV, 787 mm, ANSI, K fast, removable NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

General specificationsProduct nameEaton Bussmann series medium voltage expulsion fusePart

no.46KBR100EAN5027590481052Product Length/Depth225 millimetreProduct height76 millimetreProduct width106

millimetreProduct weight121.1 gramCompliancesANSI C37.42CertificationsContact ManufacturerProduct

TradenameNoneProduct TypeMedium voltage expulsion fuseProduct Sub TypeNoneElectrical dataAmperage Rating100

AVoltage rating46 kVCurrent characteristic typeType K - Complies with ANSI C 37-42 requirements for fast acting K

CharacteristicsRated frequency - min50 HzRated frequency - max60 HzProduct specificationsApplicationPrimary side

transformer protection, feeder protection, capacitor bank protectionStandardANSIType of terminationRemovable

buttonheadTechnical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Expulsion fuse-link, medium voltage (EC003611)Electric engineering, automation,

process control engineering / Electrical installation, device / Safety fuse systems / Safety fuse systems (unspecified) () [BAB265011])Rated current100 ARated voltage46 kVVoltage typeACRated frequency50 - 60 HzRelease characteristicKType of terminationRemovable buttonheadStandardANSI
ETIM for 46KBR100....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 46KBR100 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.