

INDUSTRIAL COMPONENT DATA

46KV 10A EXPULSION LINK 46KB10 EATON ELECTRIC

Cartridge fuse, expulsion, MT, 10 A, AC 46 kV, 787 mm, ANSI a,..

Brand: EATON - MOELLER | Manufacturer Part Number: 46KV 10A EXPULSION LINK



Manufacturer	EATON - MOELLER
MPN / Reference	46KV 10A EXPULSION LINK
Catalog number	46KB10
Category	Expulsion fuse-link, medium voltage
Minimum order	25 Pcs
Document ID	EO-148E7DE472
Generated	2026-08-06

Product Overview

Cartridge fuse, expulsion, MT, 10 A, AC 46 kV, 787 mm, ANSI a, K fast

46KV 10A EXPULSION LINK

46KB10 - Expulsion fuse-link, medium voltage, 10 A, AC 46 kV, 787 mm, ANSI, K fast

Fuse, Expulsion fuse-link, medium voltage, 10 A, AC 46 kV, 787 mm, ANSI, K fast, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories
--------------	--

Additional Product Information

Expulsion fuse-link, medium voltage, 10 A, AC 46 kV, 787 mm, ANSI, K fast
Fuse, Expulsion fuse-link, medium voltage, 10 A, AC 46 kV, 787 mm, ANSI, K fast, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

General specifications
Product name Eaton Bussmann series medium voltage expulsion fuse

Part no. 46KB10 EAN 5027590480833
Product Length/Depth 225 millimetre
Product height 76 millimetre
Product width 106 millimetre
Product weight 24.88 gram

Compliances ANSI C37.42
Certifications Contact Manufacturer

Product Tradename None
Product Type Medium voltage expulsion fuse

Product Sub Type None
Electrical data Amperage Rating 10 A

Voltage rating 46 kV
Current characteristic type Type K - Complies with ANSI C 37-42 requirements for fast acting K

Characteristics Rated frequency - min 50 Hz
Rated frequency - max 60 Hz
Product specifications Application Primary side

transformer protection, feeder protection, capacitor bank protectionStandardANSIType of terminationFixed
buttonheadTechnical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Expulsion fuse-link, medium voltage (EC003611)Electric engineering, automation,
process control engineering / Electrical installation, device / Safety fuse systems / Safety fuse systems (unspecified) ( [BAB265011])Rated current10 ARated voltage46 kVVoltage typeACRated frequency50 - 60 HzRelease
characteristicKType of terminationFixed buttonheadStandardANSI
ETIM for 46KB10 Circuit breakers and...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 46KV 10A EXPULSION LINK with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.