

INDUSTRIAL COMPONENT DATA

46KV 15AMP LINK 46TD15 46TD15 EATON ELECTRIC

Expulsion fuse-link, medium voltage, 15 A, AC 46 kV, 787 mm, AN..

Brand: EATON - MOELLER | Manufacturer Part Number: 46KV 15AMP LINK 46TD15



Manufacturer	EATON - MOELLER
MPN / Reference	46KV 15AMP LINK 46TD15
Catalog number	46TD15
Category	Expulsion fuse-link, medium voltage
Minimum order	25 Pcs
Document ID	EO-932A9D3E5E
Generated	2026-08-06

Product Overview

Expulsion fuse-link, medium voltage, 15 A, AC 46 kV, 787 mm, ANSI, T slow, style D termination

Ejection Fuse Cartridge, MT, 15 A, AC 46 kV, 787 mm, ANSI, T slow

Fuse, Expulsion fuse-link, medium voltage, 15 A, AC 46 kV, 787 mm, ANSI, T slow, Double tailed link without NEMA button head, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories

Additional Product Information

Expulsion fuse-link, medium voltage, 15 A, AC 46 kV, 787 mm, ANSI, T slow, style D termination Fuse, Expulsion fuse-link, medium voltage, 15 A, AC 46 kV, 787 mm, ANSI, T slow, Double tailed link without NEMA button head, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA Delivery program

Product range Fuse Basic function Expulsion fuse-link Field of application medium voltage Rated current [I] 15 A Rated voltage AC 46 kV Size 787 mm Description Double tailed link without NEMA button head Breaking Capacity 8 kA usable for size/applications protection of transformer primary side, feeder, capacitor bank Release characteristic [class] T slow

Standard/Approval ANSI Standards/Regulations ANSI C37-42

ETIM for 46TD15 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated current (EF000227)

15 A

Rated voltage (EF000228)

46 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Release characteristic (EF000889)

T

Type of termination (EF012540)

Double tail

Standard (EF009322)

ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 46KV 15AMP LINK 46TD15 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.