

INDUSTRIAL COMPONENT DATA

46KV 25A LK 46TB25 EATON ELECTRIC Cartridge fuse, expulsion, MT, 25 A, AC 46 kV, 787 mm, ANSI a, T slow

Brand: EATON - MOELLER | Manufacturer Part Number: 46KV 25A LK



Manufacturer	EATON - MOELLER
MPN / Reference	46KV 25A LK
Catalog number	46TB25
Category	Expulsion fuse-link, medium voltage
Minimum order	25 Pcs
Document ID	EO-796F3D9947
Generated	2026-08-06

Product Overview

Cartridge fuse, expulsion, MT, 25 A, AC 46 kV, 787 mm, ANSI a, T slow

46KV 25A LK

46TB25 - Expulsion fuse-link, medium voltage, 25 A, AC 46 kV, 787 mm, ANSI, T slow

Fuse, Expulsion fuse-link, medium voltage, 25 A, AC 46 kV, 787 mm, ANSI, T slow, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories

Additional Product Information

Expulsion fuse-link, medium voltage, 25 A, AC 46 kV, 787 mm, ANSI, T slow Fuse, Expulsion fuse-link, medium voltage, 25 A, AC 46 kV, 787 mm, ANSI, T slow, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

General specifications Product name Eaton Bussmann series medium voltage expulsion fuse Part

no. 46TB25 EAN 5027590481571 Product Length/Depth 225 millimetre Product height 76 millimetre Product width 106

millimetre Product weight 57 gram Compliances ANSI C37.42 Certifications Contact Manufacturer Product

Tradename None Product Type Medium voltage expulsion fuse Product Sub Type None Electrical data Amperage Rating 25

A Voltage rating 46 kV Current characteristic type Type T - Complies with ANSI C 37-42 requirements for slow acting T

characteristics Rated frequency - min 50 Hz Rated frequency - max 60 Hz Product specifications Application Primary side

transformer protection, feeder protection, capacitor bank protection Standard ANSI Type of termination Fixed

buttonhead Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Expulsion fuse-link, medium voltage (EC003611) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Expulsion fuse-link, medium voltage (ecl@ss13-27-14-21-28 [AGH830004]) Rated current 25 A Rated voltage 46 kV Voltage type AC Rated frequency 50 - 60 Hz Release characteristic TT Type of termination Fixed buttonhead Standard ANSI ETIM for 46TB25 Circuit breakers a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 46KV 25A LK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.