

INDUSTRIAL COMPONENT DATA

46KV 65 AMP LINK 46XAB40 EATON ELECTRIC Expulsion fuse-link, medium voltage, 40 A, AC 46 kV, 787 mm, Extra f..

Brand: EATON - MOELLER | Manufacturer Part Number: 46KV 65 AMP LINK



Manufacturer	EATON - MOELLER
MPN / Reference	46KV 65 AMP LINK
Catalog number	46XAB40
Category	Expulsion fuse-link, medium voltage
Minimum order	25 Pcs
Document ID	EO-44A6673D17
Generated	2026-08-06

Product Overview

Expulsion fuse-link, medium voltage, 40 A, AC 46 kV, 787 mm, Extra fast

Expulsion fuse cartridge, MT, 40 A, AC 46 kV, 787 mm, Extra fast

Fuse, Expulsion fuse-link, medium voltage, 40 A, AC 46 kV, 787 mm, very fast acting, fixed NEMA button head link, protection of primary side transformers, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann fuses
--------------	----------------------------------

Additional Product Information

Expulsion fuse-link, medium voltage, 40 A, AC 46 kV, 787 mm, Extra fast Fuse, Expulsion fuse-link, medium voltage, 40 A, AC 46 kV, 787 mm, very fast acting, fixed NEMA button head link, protection of primary side transformers, Breaking Capacity 8 kA Delivery program

Product range Fuse Basic function Expulsion fuse-link Field of application medium voltage Rated current [I] 40 A Rated voltage AC 46 kV Size 787 mm Description fixed NEMA button head link Breaking Capacity 8 kA usable for size/applications protection of primary side transformers Release characteristic [class] very fast acting ETIM for 46XAB40 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated current (EF000227)

40 A

Rated voltage (EF000228)

46 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Release characteristic (EF000889)

Other

Type of termination (EF012540)

Fixed buttonhead

Standard (EF009322)

ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 46KV 65 AMP LINK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.