

INDUSTRIAL COMPONENT DATA

46KV 65A EXPULSION LINK 46KB65 EATON ELECTRIC

Expulsion fuse-link, medium voltage, 7.5 A, AC 15 kV, 533 mm, ..

Brand: EATON - MOELLER | Manufacturer Part Number: 46KV 65A EXPULSION LINK



Manufacturer	EATON - MOELLER
MPN / Reference	46KV 65A EXPULSION LINK
Catalog number	46KB65
Category	Expulsion fuse-link, medium voltage
Minimum order	10 Pcs
Document ID	EO-07F74A9EBD
Generated	2026-08-06

Product Overview

Expulsion fuse-link, medium voltage, 7.5 A, AC 15 kV, 533 mm, ANSI, K fast, style B termination

46KV 65A EXPULSION LINK

Fuse, Expulsion fuse-link, medium voltage, 65 A, AC 46 kV, 787 mm, ANSI, K fast, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series medium voltage expulsion fuse Catalog Number 46KB65 EAN 5027590480987

Product Length/Depth 787 mm Product Height 19.1 mm Product Width 19.1 mm Product Weight 118.1 g Compliances ANSI C37.42 Electrical data

Amperage Rating 65 A Voltage rating 46 kV Voltage type AC Current characteristic type Type K - Complies with ANSI C 37-42 requirements for fast acting K Characteristics Rated frequency - min 50 Hz Product specification

Construction size 787 mm Standard ANSI Type of termination Fixed buttonhead Color Yellow

ETIM for 46KB65 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated current (EF000227)

65 A

Rated voltage (EF000228)

46 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Release characteristic (EF000889)

K

Type of termination (EF012540)

Fixed buttonhead

Standard (EF009322)

ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 46KV 65A EXPULSION LINK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.