

INDUSTRIAL COMPONENT DATA

46KV 75A EXPULSION LINK 46TB75 EATON ELECTRIC

Fuse-link, high speed, 315 A, DC 4000 V, size 2, 75 x 155 x 41..

Brand: EATON - MOELLER | Manufacturer Part Number: 46KV 75A EXPULSION LINK



Manufacturer	EATON - MOELLER
MPN / Reference	46KV 75A EXPULSION LINK
Catalog number	46TB75
Category	Expulsion fuse-link, medium voltage
Minimum order	10 Pcs
Document ID	EO-8D20F6285E
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 315 A, DC 4000 V, size 2, 75 x 155 x 414 mm, aR, IEC, single indicator, dual body

46KV 75A EXPULSION LINK

Expulsion fuse-link, medium voltage, 75 A, AC 46 kV, 787 mm, ANSI, T slow

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series medium voltage expulsion fuse Catalog Number 46TB75 EAN 5027590481670

Product Length/Depth 225 mm Product Height 76 mm Product Width 106 mm Product Weight 0.133 g Certifications

ANSI/IEEE Std C37.42 Electrical data

Amperage Rating 75 A Voltage rating 46 kV Voltage type AC Current characteristic type Type T - Complies with ANSI C 37-42 requirements for slow acting T characteristics Rated frequency - min 50 Hz Product specification

Construction size 787 mm Standard ANSI Type of termination Fixed buttonhead Color Green

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 46KV 75A EXPULSION LINK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.