

## INDUSTRIAL COMPONENT DATA

# 46KBR7.5 46KBR7-5 EATON ELECTRIC Expulsion fuse-link, medium voltage, 7.5 A, AC 46 kV, 787 mm, ANSI, K fast

Brand: EATON - MOELLER | Manufacturer Part Number: 46KBR7.5



|                 |                                     |
|-----------------|-------------------------------------|
| Manufacturer    | EATON - MOELLER                     |
| MPN / Reference | 46KBR7.5                            |
| Catalog number  | 46KBR7-5                            |
| Category        | Expulsion fuse-link, medium voltage |
| Minimum order   | 25 Pcs                              |
| Document ID     | EO-3E345BFFB1                       |
| Generated       | 2026-08-06                          |

## Product Overview

46KV 7.5A REMOVABLE B/H EXPULSION LINK

46KBR7.5 - Expulsion fuse-link, medium voltage, 7.5 A, AC 46 kV, 787 mm, ANSI, K fast

Fuse, Expulsion fuse-link, medium voltage, 7.5 A, AC 46 kV, 787 mm, ANSI, K fast, removable NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path

EATON - MOELLER &gt; Bussmann Series Medium Voltage fuses and accessories

## Additional Product Information

Expulsion fuse-link, medium voltage, 7.5 A, AC 46 kV, 787 mm, ANSI, K fast Fuse, Expulsion fuse-link, medium voltage, 7.5 A, AC 46 kV, 787 mm, ANSI, K fast, removable NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

General specifications Product name Eaton Bussmann series medium voltage expulsion fuse Part

no. 46KBR7.5 EAN 5027590481229 Product Length/Depth 787 millimetre Product height 19.1 millimetre Product width 19.1 millimetre Product weight 25.24 gram Compliances ANSI C37.42 Certifications Contact Manufacturer Product

Tradename None Product Type Medium voltage expulsion fuse Product Sub Type None Electrical data Amperage Rating 7.5

A Voltage rating 46 kV Current characteristic type Type K - Complies with ANSI C 37-42 requirements for fast acting K

Characteristics Rated frequency - min 50 Hz Rated frequency - max 60 Hz Product specifications Application Primary side transformer protection, feeder protection, capacitor bank protection Standard ANSI Type of termination Removable

buttonhead Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Expulsion fuse-link, medium voltage (EC003611) Electric engineering, automation,

process control engineering / Electrical installation, device / Safety fuse systems / Safety fuse systems (unspecified) ([email protected]  
protected] [BAB265011])Rated current7.5 ARated voltage46 kVVoltage typeACRated frequency50 - 60 HzRelease  
characteristicKType of terminationRemovable buttonheadStandardANSI  
ETIM for 46KBR7...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 46KBR7.5 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.