

INDUSTRIAL COMPONENT DATA

4A 1200 VAC 750 VDC (10) 4HD36 EATON ELECTRIC

Fuse-link, high speed, 10 A, AC 1200 V, DC 750 V, 22 x 138 mm,..

Brand: EATON - MOELLER | Manufacturer Part Number: 4A 1200 VAC 750 VDC (10)



Manufacturer	EATON - MOELLER
MPN / Reference	4A 1200 VAC 750 VDC (10)
Catalog number	4HD36
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-C16C819D24
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 10 A, AC 1200 V, DC 750 V, 22 x 138 mm, gL/gG, BS

4A 1200 VAC 750 VDC (10)

Fuse, Fuse-link, high speed, 4 A, AC 1200 V, DC 750 V, 22 x 138 mm, gL/gG, BS, offset bolted tags (slotted), traction, BS, Breaking Capacity 80 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, high speed, 4 A, AC 1200 V, DC 750 V, 80 kA, 22 x 138 mm, gL/gG, BS
Fuse, Fuse-link, high speed, 4 A, AC 1200 V, DC 750 V, 22 x 138 mm, gL/gG, BS, offset bolted tags (slotted), traction, BS, Breaking Capacity 80 kA
Delivery program

Product rangeFuseBasic functionFuse-linkField of applicationhigh speedRated current [I]4 ARated voltageAC 1200 VDC 750 VSize22 x 138 mmUtilization categorygL/gGBreaking Capacity80 kAusable forsize/applicationtractionStandard/ApprovalBSShapeoffset bolted tags (slotted)Standards/RegulationsBSTechnical dataETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015])Construction sizeOtherRated current4 ARated voltage1200 VVoltage typeAC/DCRated switching capacity80

kAUtilization categorygL/gG (cable protection/equipment protection)Type of fuse status indicatorNoneInsulated metal gripping lugs (IMGL)No
ETIM for 4HD36 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
Other
Type of current (EF000143)
AC/DC
Rated voltage AC (EF007682)
1200 V
Rated voltage DC (EF012281)
750 V
Rated current (EF000227)
4 A
Utilization category according to IEC 60269 (EF002572)
gG (cable protection/equipment protection)
Breaking capacity (EF005617)
80 k...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 4A 1200 VAC 750 VDC (10) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.