

INDUSTRIAL COMPONENT DATA

4A 440V AC BS88 FUSE NS4 EATON ELECTRIC Fuse-link, low voltage, 710 A, AC 550 V, DC 250 V, BS88, BS, IEC

Brand: EATON - MOELLER | Manufacturer Part Number: 4A 440V AC BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	4A 440V AC BS88 FUSE
Catalog number	NS4
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-D93AACA6BD
Generated	2026-08-06

Product Overview

Fuse-link, low voltage, 710 A, AC 550 V, DC 250 V, BS88, BS, IEC

4A 440V AC BS88 FUSE

Fuse-link, low voltage, 4 A, AC 440 V, 80 kA, BS88/F1, 15 × 62 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 4 A, AC 440 V, BS88/F1, 15 x 62 mm, gL/gG, BS, offset bladed tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, low voltage, 4 A, AC 440 V, 80 kA, BS88/F1, 15 × 62 mm, gL/gG, BS Fuse, Fuse-link, low voltage, 4 A, AC 440 V, BS88/F1, 15 x 62 mm, gL/gG, BS, offset bladed tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 4 A Rated voltage AC 440 V Construction size BS88/F1 Size 15 × 62 mm Utilization category gL/gG Breaking Capacity 80 kA Suitable for size/applications general industrial applications Standard/Approval BS Shape offset bladed tags Standards/Regulations BS88-2 IEC 60269-2 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015]) Construction size Other Rated current 4 A Rated voltage 440 V Voltage type AC Rated switching capacity 80 kA Utilization category gL/gG (cable protection/equipment protection) Type of fuse status indicator None Insulated metal

gripping lugs (IMGL)No
ETIM for NS4 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Fuse system E
Fuse construction type according to IEC 60269 (EF015865)
F1
Type of current (EF000143)
AC
Rated voltage AC (EF007682)
440 V
Rated current (EF000227)
4 A
Utilization category according to IEC 60269 (EF002572)
gG (cable protection/equipment protection)
Bre...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 4A 440V AC BS88 FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.