

INDUSTRIAL COMPONENT DATA

4AMP 550V AC BS88 gG FUSE AAO4 EATON ELECTRIC

Fuse-link, LV, 4 A, AC 550 V, BS88/A2, 14 x 85 mm, gL/gG, BS

Brand: EATON - MOELLER | Manufacturer Part Number: 4AMP 550V AC BS88 gG FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	4AMP 550V AC BS88 gG FUSE
Catalog number	AAO4
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-E0D4ADF1FB
Generated	2026-08-06

Product Overview

Fuse-link, LV, 4 A, AC 550 V, BS88/A2, 14 x 85 mm, gL/gG, BS

4AMP 550V AC BS88 gG FUSE

Fuse, Fuse-link, low voltage, 4 A, AC 550 V, BS88/A2, 14 x 85 mm, gL/gG, BS, offset bolted tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder CM32F RS32

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number AAO4 EAN 5027590491617 UPC 051712838474 Product Length/Depth 85 mm Product Height 14 mm Product Width 14 mm Product Weight 20.1 g

Compliances RoHS Compliant Electrical data

Amperage Rating 4 A Voltage rating 550 V Voltage type AC Breaking capacity 80 kA Class Class gG/gL Compatible fuse holder

Suitable for CM32F Camaster fuse holder

RS32 Red spot fuse holder Product specifications

Fuse type AAO Fitted with: Offset bolted tags Construction BS88/A2

ETIM for AAO4 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)
Fuse system E
Fuse construction type according to IEC 60269 (EF015865)
A2
Type of current (EF000143)
AC
Rated voltage AC (EF007682)
550 V
Rated current (EF000227)
4 A
Utilization category according to IEC 60269 (EF002572)
gG (cable protection/equipment protection)
Breaking capacity (EF005617)
80 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
None
Power loss at rated current (EF012389)
1.4 W
Mounting holes (EF021553)
M5
Centre-to-centre distance of connections (EF021151)
73 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 4AMP 550V AC BS88 gG FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.