

INDUSTRIAL COMPONENT DATA

500 AMP THYRISTOR FUSE 1 500CFMM EATON ELECTRIC

Fuse-link, high speed, 350 A, AC 240 V

Brand: EATON - MOELLER | Manufacturer Part Number: 500 AMP THYRISTOR FUSE 1



Manufacturer	EATON - MOELLER
MPN / Reference	500 AMP THYRISTOR FUSE 1
Catalog number	500CFMM
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-75D1FCB198
Generated	2026-08-04

Product Overview

Fuse-link, high speed, 350 A, AC 240 V

500 AMP THYRISTOR FUSE 1

Fuse, Fuse-link, high speed, 500 A, AC 690 V, DC 450 V, BS88, 83 x 136 mm, aR, BS, centre-bolted tags (dual barrel), 110 mm fixing centres, dual-barrel, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 350 A, AC 240 V Fuse, Fuse-link, high speed, 350 A, AC 240 V, cylindrical with centre-bolted tags [Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I] 350 A Rated voltage AC 240 V Shape cylindrical with centre-bolted tags , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015]) Construction size Other Rated current 350 A Rated voltage 240 V Voltage type AC Rated switching capacity kA Utilization category Other Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No]

ETIM for 500CFMM Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
Other
Type of current (EF000143)
AC/DC
Rated voltage AC (EF007682)
690 V
Rated voltage DC (EF012281)
450 V
Rated current (EF000227)
500 A
Utilization category according to IEC 60269 (EF002572)
aR (accompanied semiconductor protection)
Breaking capacity (EF005617)
200 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
None
Power loss at rated current (EF012389)
100 W
Mounting holes (EF021553)
M10
Centre-to-centre distance of connections (EF021151)
110 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 500 AMP THYRISTOR FUSE 1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.